

PARKER DIVISION-OXY METAL INDUSTRIES CORP -- ACCU-PEN PR-2 -- 6850-00-782-2740

=====
Product Identification
=====

Product ID:ACCU-PEN PR-2

MSDS Date:01/01/1985

FSC:6850

NIIN:00-782-2740

Kit Part:Y

MSDS Number: BFPPL

=== Responsible Party ===

Company Name:PARKER DIVISION-OXY METAL INDUSTRIES CORP

Address:32100 STEPHENSON HWY

City:MADISON HEIGHTS

State:MI

ZIP:48071-1003

Country:US

Emergency Phone N

um:NONE

CAGE:HO255

=== Contractor Identification ===

Company Name:OXY METAL INDUSTRIES CORP, PARKER CO

Address:32100 STEPHENSON HWY

Box:City:MADISON HEIGHTS

State:MI

ZIP:48071-1003

Country:US

CAGE:45738

Company Name:PARKER DIVISION-HOOKER CHEMICALS & PLASTICS CORP

Address:32100 STEPHENSON HWY

Box:City:MADISON HEIGHTS

State:MI

ZIP:48071-1003

Country:US

CAGE:HO255

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS:71-55-6
RTECS #:KJ2975000
Fraction by Wt: 75%
OSHA PEL:350 PPM/450 STEL
ACGIH TLV:350 PPM/450STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS
Ozone Depleting Chemical:1

Ingred Name:DICHLORODIFLUOROMETHANE (SARA III)
CAS:75-71-8
RTECS #:PA8200000
Fraction by Wt: 25%
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS
Ozone Depleting Chemical:1

=====
Hazards Identification
=====

Effects of Overexposure:MILD EYE IRRITATI
ON.ANESTHESIA MAY OCCUR IN THE
RANGE OF 500 TO 1000 PPM

=====
First Aid Measures
=====

First Aid:EYES/SKIN-FLUSH WITH WATER.GET MEDICAL ATTENTION IF INJURY
DEVELOPS.IF SWALLOWED-INDUCE VOMITING,CALL PHYSICIAN.INHALATION-IF
BREATHING STOPS,GIVE ARTIFICIAL RESPIRATION.GET MEDICALHELP.MOVE TO
FRESH AIR

=====
Fire Fighting Measures
=====

Flash Point:NONE T.C.C.
Extinguishing Media:WATER FOG
Fire Fighting Pro
cedures:USE SELF CONTAINED BREATHING GEAR
Unusual Fire/Explosion Hazard:AREA AEROSOL CANS-MAY EXPLODE WHEN HEATED

=====
Accidental Release Measures
=====

Spill Release Procedures:SMALL LEAKS-MOP UP OR SOAK UP,IMMEDIATELY
REMOVE TO OUTSIDE,LARGE SPILLS-EVACUATE AREA.CONTAIN
LIQUID,TRANSFER TO CLOSED METAL CONTAINER

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN CHEMICAL AREA.HANDLE WITH
REAS

ONABLE CARE.AVOID BREATHING VAPORS

Other Precautions:FOR DOCTOR-OVEREXPOSURE TO CHLORINATED SOLVENTS IF ACCOMPANIED BY ANOXIA MAY TEMPORARILY INCREASE CARDIAC IRRITABILITY.MAINTAIN ADEQUATE OXYGENATION UNTIL RECOVERY.SEE SUPPLEMENTAL DATA.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF CONTAINED AS NEEDED TO LIMIT CONCENTRATION TO TLV.

Ventilation:LOCAL RECOMMENDED

Protective Gloves:NOT NEEDED

Eye Protection:SAFETY GLASSES

Other

Protective Equipment:NO SPECIAL PROTECTIVE CLOTHING

Supplemental Safety and Health

AVOID SYMPATOMIMETIC AMINES,SUCH AS EPINEPHRINE,WHICH MAY PRECIPITATE ARRHYTHMIAS.

=====
===== Physical/Chemical Properties =====

HCC:V2

Boiling Pt:=73.9C, 165.F

Vapor Pres:100

Vapor Density:4.55

Spec Gravity:1.321

Solubility in Water:VERY SLIGHT

Appearance and Odor:COLORLESS LIQUID

Percent Volatiles by Volume:100

=====
===== Stability and Reactivity Data =====

Sta

bility Indicator/Materials to Avoid:YES

WATER-SLOW HYDROLYSIS PRODUCES CORROSIVE ACID

Stability Condition to Avoid:OPEN FLAMES OR OTHER HIGH TEMPERATURE SOURCE

Hazardous Decomposition Products:HYDROGEN CHLORIDE,PHOSGENE,CHLORINE

=====
===== Disposal Considerations =====

Waste Disposal Methods:SEND SOLVENT TO RECLAIMER SEE ALSO MANUFACTURING CHEMISTS ASSOCIATION SAFETY DATA SHEET SD-90.

Disclaimer (provided with this information by the compiling agencies):

T

his information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.