View NSN Online: https://aerobasegroup.com/nsn/6850-00-782-2740

MET-L-CHEK COMPANY -- D-701 DEVELOPER -- 6850-00-782-2740

=========== Product Identification =============

Product ID:D-701 DEVELOPER

MSDS Date:03/15/1989

FSC:6850

NIIN:00-782-2740

Kit Part:Y

MSDS Number: BFPPV === Responsible Party ===

Company Name: MET-L-CHEK COMPANY

Address:1639 EUCLID STREET

City:SANTA MONICA

State:CA

ZIP:90404-3723

Country:US

Info Phone Num:213-450-1111

Emergency Phone Num:213-450-1111

CAG E:98733

=== Contractor Identification ===

Company Name: MET-L-CHEK COMPANY

Address:1639 EUCLID ST

Box:00000

City:SANTA MONICA

State:CA ZIP:90404 Country:US

Phone:310-450-1111/FAX 310452-4046

CAGE:98733

======= Composition/Information on Ingredients ========

Ingred Name: METHYL CHLOROFORM (1,1,1-TRICHLOROEHANE) (SARA III)

CAS:71-55-6

RTECS #:KJ2975000 Fraction by Wt: 5.00%

OSHA PEL:1000PPM (PROPANE)

ACGIH TLV:ASPHYXIANTS

Ingred Name: INERT MATERIAL

Fraction by Wt: 10.0%

ACGIH TLV:NO

T SPECIFIED
======================================
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:MATERIAL IS PRIMARILY CNS DEPRESSANT. INHALATION CAN CAUSE IRRITATION OF RESP TRACT SYSTEM.SKIN OR EYES CONTACT MAY RESULT IN DISCOMFORT,PAIN AND IRRITATION. SWALLOWING MAY RESULT IN IRRITATION OF THE MOUTH AND GI TRACT. Effects of Overexposure:EYES: MAY CAUSE IRRITATION; SKIN: SLIGHT IRRITATION ON CONTACT WITH LIQUID.MAY CAUSE DERMATITIS; INHALATION: VAPORS MAY IRRITATE RESP TRACT. CAUSES DIZZINESS,HEADACHE,DISCOMFORT,PAIN OR IRRITATION OF MOUTH. MAY CAUSE NAUSEA WITH VOMITING. INGESTION: MAY CAUSE IRRITATION OF GI TRACT.
Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT. MAY CAUSE DERMATITIS.
======================================
First Aid:EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES.GET MEDICAL HELP IF IRRITATION OCCURS OR PERSISTS; SKIN: FLUSH WITH WATER.WASH

First Aid:EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES.GET MEDICAL HELP IF IRRITATION OCCURS OR PERSISTS; SKIN: FLUSH WITH WATER.WASH WITH LUKE WARM WATER & SOAP.GET MEDICAL HELP FOR PERSISTING IRRITATION; IN HALATION: REMOVE TO FRESH AIR.IF NOT BREATHING,GIVE ARTIFICIAL RESPIRATION.GET MED ASST IF NEEDED; INGESTION: IF SWALLOWED, DO NOT INDUCE VOMITING. IMMEDIATELY GET MEDICAL ASSISTANCE.


Flash Point:NONE Lower Limits:7 % Upper Limits:15 %

Extinguishing Media: PER MFR, USE WATER, DRY CHEMICAL OR CARBON DIOXIDE.

Fire Fighting Procedures:WEAR NIOSH-APPROVED PRESSURE DEMAND SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:PER MANUFACTURER,VAPORS CONCENTRATED IN CONFINED/POORLY VENTILATED AREA CAN BE IGNITED UPON CONTACT WITH HIGH ENERGY SPARK,FLAME OR HIGH INTENSITY HEAT SOURCE.

======== Accidental Release Measures ===========



========== Handling and Storage ============

Handling and Storage Precautions:KEEP AWAY FROM SOURCES OF HEAT/IGNITION.STORE IN COOL,DRY & VENTILATED AREA.DO NOT STORE NEAR OXIDI

ZING MATERIAL; AVOID PHYSICAL DAMAGE TO CONTAINERS.

Other Precautions:MINIMIZE SKIN CONTACT.AVOID BREATHING VAPORS.USE ONLY WITH ADEQUATE VENTILATION.AVOID PROLONGED & REPEATED CONTACT WITH SKIN.DO NOT SWALLOW.VAPORS ARE HEAVIER THAN AIR WILL COLLECT IN LOW AREAS.DO NOT ENTER WITHOUT RESPIRATORY PROTECTION.

===== Exposure Controls/Personal Protection ========

Respiratory Protection: NOT NEEDED IN NORMAL CONDITIONS OR USES WHEN VAPORS/MIST CONCENTRATIONS ARE BELOW

TLV/PEL LIMITS.WEAR NIOSH

APPROVED ORGANIC VAPOR CHEMICAL CARTRIDGE OR CANISTER TYPE RESPIRATOR WHEN TLV EXCEEDS OR IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL

Ventilation:LOCAL EXHAUST OR MECHANICAL(GENERAL) TO MAINTAIN TLV OR BELOW TLV LIMITS.

Protective Gloves:VITON

Eye Protection: SPLASH-PROOF GOGGLES

Other Protective Equipment: CHEMICAL RESISTANT APRON TO PREVENT CLOTHING/SKIN CONTACT.

Work Hygienic Practices: WASH HANDS WITH SOAP & WATER BEFORE EATING, SMOKING OR USING

TOILET FACILITIES;DO NOT EAT/DRINK IN VAPOR CONTMNTD AREA.

Supplemental Safety and Health

NSN IS A 3 PARTS KIT OF TYPE I,METH C,LVL 3 OF MIL-I-25135,REV D;KITCONSISTS OF 3 AEROSOL CANS OF PENETRANT, 3 AEROSOL CANS OF REMOVER, & 3 AEROSOL CANS OF DEVELOPER;I/A/W QPL-25135-15,THE MET-L-CHEK MAY HAVE FP-95,FP-98,OR FP-99 PENETRANT,D-701 OR D-703 DEVELOPER AND R-501 REMOVER;KEY1:J7;THIS ENTRY IS OF D-701 DEVL.

======== Physical/Chemical Properties ===========

HCC:V3

Boiling Pt:=72.C, 161.6F Vapor Pres:135MM@25C

Vapor Density:4.54

Spec Gravity: 1.300 TO 1.320

Evaporation Rate & Evaporation R

Solubility in Water: NEGLIGIBLE

Appearance and Odor:MILKY WHITE LIQUID WITH ETHER-LIKE ODOR

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES
OXIDIZING MATERIAL, CAUSTIC SODA, CAUSTIC POTASH.
Stability Condition to Avoid:SOURCE OF HEAT/IGNITION. AVOID EXPOSURE TO
OXIDIZING MATE

RIALS.

Hazardous Decomposition Products:HYDROGEN CHLORIDE AND POSSIBLY TRACES OF PHOSGENS.

======= Disposal Considerations ============

Waste Disposal Methods:PER MANUFACTURER, THE WASTE MUST BE DISPOSED OF IN A PERMITTED HAZARDOUS WASTE MANAGEMENT FACILITY IN FULL COMPLIANCE WITH ALL FEDERAL STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.