

ESSEX CHEM. CORP. -- PRO-SEAL 700 FIREWALL SEALANT -- 8030-00-783-8886

=====
Product Identification
=====

Product ID:PRO-SEAL 700 FIREWALL SEALANT

MSDS Date:01/01/1987

FSC:8030

NIIN:00-783-8886

Kit Part:Y

MSDS Number: BFPST

=== Responsible Party ===

Company Name:ESSEX CHEM. CORP.

Address:19451 SUSANA RD

City:COMPTON

State:CA

ZIP:90221-5713

Country:US

CAGE:LO918

=== Contractor Identification ===

C

Company Name:ESSEX CHEM. CORP.SPECIALTY CHEMS.DIV.

Address:19451 SUSANA RD

Box:City:COMPTON

State:CA

ZIP:90221-5713

Country:US

CAGE:LO918

Company Name:ESSEX CHEMICAL CORP PRO-SEAL DIV

Address:19451 SUSANA RD

Box:City:COMPTON

State:CA

ZIP:90221-5713

Country:US

Phone:310-537-7600

CAGE:83527

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 9%

Other REC Limits:NONE RECOMM

ENDED
OSHA PEL:200 PPM
ACGIH TLV:200 PPM/300STEL;9394
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ISOBUTYL KETONE (HEXONE) (SARA III)
CAS:108-10-1
RTECS #:SA9275000
Fraction by Wt: 28%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:50 PPM/75 STEL; 9394
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
Hazards Identification =====

Effects of Overexposure:MAY BE IRRITATING TO SKIN AND MUCOUS SURFACES.MAY CAUSE NARCOSIS

=====
First Aid Measures =====

First Aid:WASH THOROUGHLY AFTER HANDLING,INHALATION-REMOVE TO FRESH AIR. IF INGESTED,CALL PHYSICIAN IMMEDIATELY

=====
Fire Fighting Measures =====

Flash Point:54 F SCC 12 C
Lower Limits:1.8
Upper Limits:11.5
Extinguishing Media:CO*2,FOAM,DRY CHEMICAL
Fire Fighting Procedures:USE OF WATER NOT RECOMMENDED
Unusual Fire/Explosion Hazard:RED LABEL SOLVENTS

=====
Accidental Release Measures =====

Spill Release Procedures:CLEAN UP WASTE WITH SOLVENT AND RAGS

=====
Handling and Storage =====

Handling and Storage Precautions:STORE IN CLOSED CONTAINERS BELOW 80 F AVOID OPEN FLAMES AND SPARKS WHEN USING.
Other Precautions:RED LABEL MATERIAL.

=====
Exposure Controls/Personal Protection =====

Respiratory Protection:USE W/ADEQUATE VENTILATION.
Protective Gloves:BUNA-RUBBER
Eye Protection:FACE SHIELD
Other Pr

Protective Equipment: APRON OR COVERALLS
Supplemental Safety and Health
MEK 175 F 79 C

===== Physical/Chemical Properties =====

HCC:F3
Boiling Pt:B.P. Text:MEK 175 F
Vapor Pres:71
Vapor Density:2.5
Spec Gravity:1.5
Evaporation Rate & Reference:4.0
Solubility in Water:35% EXTRACT
Appearance and Odor:BLACK-KETONE ODOR
Percent Volatiles by Volume:50

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:AVOID EXPOSURE TO HIGH TEMPERATURE
Hazardous Decomposition Products:HCMO,CO,CO*2, HCL ETC UPON COMBUSTION

===== Disposal Considerations =====

Waste Disposal Methods:BURN WASTE

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.