

TELEDYNE OSTER -- BESTOIL -- 9150-00-785-3769

=====  
Product Identification  
=====

Product ID: BESTOIL  
MSDS Date: 01/01/1987  
FSC: 9150  
NIIN: 00-785-3769  
MSDS Number: BFPTQ  
=== Responsible Party ===  
Company Name: TELEDYNE OSTER  
Emergency Phone Num: 216-943-3500  
CAGE: 45168  
=== Contractor Identification ===  
Company Name: TELEDYNE OSTER  
CAGE: 45168

=====  
Composition/Information on Ingredients  
=====

Ingred Name: SULFURIZED MINERAL OIL (CAS NO.69029-75-0)  
Fraction by Wt: 90.5%  
  
Ingred Name: SULFURIZED POLY BUTENE (CAS NO.6829-54-7)  
Fraction by Wt: 6.5%  
  
Ingred Name: SULFURIZED FAT (CAS NO.61790-49-6)

=====  
Hazards Identification  
=====

Effects of Overexposure: EYES: SEV IRRIT, RED, TEAR. SKIN: PRLNG/RPTD  
CNTCT: MOD IRRIT, DEFAT, DERMAT. INH/INGEST: NAUSEA, VOMIT, DIARR

=====  
First Aid Measures  
=====

First Aid: SKIN: THO  
ROUGHLY WASH W/WATERLESS HAND CLEANER, THEN SOAP &  
WATER - DISCARD SOAKED CLOTHING. EYES: FLUSH W/LG AMTS OF WATER FOR  
15 MIN, GET MEDICAL ATTN. INGEST: DO NOT INDUCE VOMITING - SEEK  
MEDICAL HE LP. INH: REMOVE TO FRESH AIR, USE OXYGEN IF NEC.

=====  
Fire Fighting Measures  
=====

Flash Point: 300F COC  
Extinguishing Media: FOAM, CO\*2, DRY CHEMICAL  
Fire Fighting Procedures: WEAR SCBA W/FULL FACE PIECE IN POSITIVE  
PRESSURE DEMAND  
Unusual Fire/Explosion Ha

zard:VAP HEAVIER THAN AIR;MAY TRAVEL ALONG  
GROUND & BE IGNIT AT LOCATIONS DISTANT FROM MATERIAL USE.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. CONFINE  
SPILL. PUMP LIQUID TO STORAGE. ABSORB LIQUID W/SAND,CLAY,EARTH  
FLOOR ABSORBENT.

===== Handling and Storage =====

Handling and Storage Precautions:TREAT AS WITH NORMAL PETROLEUM CUTTING  
OIL.

Other Precautions:

BESTOIL DOES NOT CONTAIN: AMINES

NITRITES,NITROAMINES, TRIETHANE AMINE,SPECIFICALLY

DIETHANOLNITROSAMINE, POLYCHLORINATED BIPHENYLS,CARCINOGENIC  
MATERIALS OR POLYNUCLEAR AROMATIC COMPOUNDS

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPRVD AIR-SUPP RESP IF EXPOSURE  
CONDITIONS REQUIRE

Ventilation:LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV.

Protective Gloves:NEOP/NITRILE

Eye Protection:CHEMICAL SPLASH GOGGLES

Other Prote

ctive Equipment:WEAR IMPERVIOUS CLOTHING & BOOTS

Supplemental Safety and Health

(DATE OF ISSUE: 11-20-85)

===== Physical/Chemical Properties =====

HCC:V6

Spec Gravity:0.91

Solubility in Water:NO

Appearance and Odor:DARK,CLEAR LIQUID; MINERAL OIL ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS (PEROXIDES,CITRIC ACID,CHLORINE,O\*2)

Hazardous Decomposition Products:USUAL FOR PE

# TROLEUM PRODUCTS

## ===== Disposal Considerations =====

Waste Disposal Methods: BURN UNDER CONTROLLED CONDITIONS OR DEPOSIT IN DISPOSAL SITE. THESE METHODS MUST BE IAW FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.