View NSN Online: https://aerobasegroup.com/nsn/8010-00-787-8856

## GROW GROUP INC U S PAINT DIV -- MIL-P-38336 -- 8010-00-787-8856

=========== Product Identification =============

Product ID:MIL-P-38336 MSDS Date:01/01/1985

FSC:8010

NIIN:00-787-8856

MSDS Number: BFPVW === Responsible Party ===

Company Name: GROW GROUP INC US PAINT DIV

Address:831 S 21ST ST City:SAINT LOUIS

State:MO

ZIP:63103-3043 Country:US

Info Phone Num:314-621-0525 / FAX 314-621-0722

**Emergency Phone Num:31** 

4-621-0525 CAGE:90608

=== Contractor Identification ===

Company Name: US PAINT CORPORATION

Address:831 SOUTH 21ST STREET

Box:City:ST LOUIS

State:MO

ZIP:63103-3092 Country:US

Phone:314-621-0525

CAGE:90608

======= Composition/Information on Ingredients ========

Ingred Name:ETHYL ALCOHOL (ETHANOL)

CAS:64-17-5

RTECS #:KQ6300000 Fraction by Wt: 24.0% OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

Ingred Name:2-ETHOXYETHANOL (EGEE) (SARA III)

CAS:110-80-5

RTECS #:KK8050000

Fraction by Wt:

ACGIH TLV:S, 5 PPM; 9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS ========== Hazards Identification =============== Effects of Overexposure: EYE AND UPPER RESPIRATORY IRRITANT First Aid:IF EXPOSED TO EXCESS VAPOR, REMOVE TO FRESH AIR AND SEEK MED. ATT.IF SLASHED ON SKIN OR IN EYES, FLUS W/LG AMT OF WATER & SEEK IMMEDIATE MED ATT.IF INGESTED, DO NOT INDUCE VOMITING BUT SEEK IMMED MEDICA L ATTN. ============ Fire Fighting Measures ========================= Flash Point:45 F TCC Lower Limits: 2.6 Extinguishing Media: DRY CHEMICAL OR FOAM Unusual Fire/Explosion Hazard: DO NOT EXPOSE OR OPEN FLAME ======== Accidental Release Measures ============ Spill Release Procedures: AFFECTED AREA SHOULD BE TREATED WITH AN ABSORBING MATERIAL AND THEN PLACED IN A TIGHTLY CLOSED CONTAINER. ============ Handling and Storage ============= ===== Handling and Storage Precautions: KEEP AWAY FROM EXCESS HEAT, SPARKS, AND FLAME. ====== Exposure Controls/Personal Protection ======== Respiratory Protection: CHARCOAL BASE FOR SOLVENT VAPOR & NIOSH/MSHA **APPROVED** Ventilation: LOCAL EXHAUST-SUFFICIENT TO KEEP AIR SUPPLY BELOW TLV Protective Gloves: RUBB OR POLYETH Eye Protection: GOGGLES Other Protective Equipment: HYPERSENSITIVE PERSONS SHOULD WEAR

12.0%

OSHA PEL:S,200 PPM

PROTECTIVE CREAMS
Supplemental Safety and Health

VAPOR DENSITY IF HEA

VIER THAN AIR.
========== Physical/Chemical Properties ==========
HCC:F2 Boiling Pt:B.P. Text:167 TO 279F Vapor Pres:3. Spec Gravity:1.01 Evaporation Rate & Dr. Reference:1.0 N-BUAC Solubility in Water:APPRECIABLE Appearance and Odor:OFF WHITE-ALCOHOL Percent Volatiles by Volume:39.0
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES OXIDIZING MATERIALS Stability Condition to Avoid:EXCESS HEAT Hazardous Decompositi on Products:NONE
====== Disposal Considerations ===========
Waste Disposal Methods:IN ACCORDANCE W/LOCAL STATE & FED CODES.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this docu

ment should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.