

SPRAGUE PRODUCTS CO -- 00060 JET PAK UNIT, LAB NO.: 45947 -- 4940-00-803-6444
===== Product Identification =====

Product ID:00060 JET PAK UNIT, LAB NO.: 45947

MSDS Date:08/24/1989

FSC:4940

NIIN:00-803-6444

MSDS Number: BFQCP

=== Responsible Party ===

Company Name:SPRAGUE PRODUCTS CO

Address:87 MARSHALL ST

City:NORTH ADAMS

State:MA

ZIP:01247-2402

Country:US

Info Phone Num:216-292-7400

Emergency Ph

one Num:216-292-7400

CAGE:80183

=== Contractor Identification ===

Company Name:SPRAGUE PRODUCTS CO

Address:87 MARSHALL ST

Box:City:NORTH ADAMS

State:MA

ZIP:01247-2402

Country:US

CAGE:80183

===== Composition/Information on Ingredients =====

Ingred Name:TRICHLOROFLUOROMETHANE (CFC-11) (SARA III)

CAS:75-69-4

RTECS #:PB6125000

Fraction by Wt: 15%

OSHA PEL:1000 PPM

ACGIH TLV:C, 1000 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ozone Depleting Chemical:1

Ingred Name:DICHL

ORODIFLUOROMETHANE (SARA III)

CAS:75-71-8

RTECS #:PA8200000

Fraction by Wt: 85%

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ozone Depleting Chemical:1

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:CHRONIC: REPORTS HAVE ASSOCIATED
REPEATED AND PROLONGED OVEREXPOSURE TO SOLVENTS WITH PER
MANENT
BRAIN AND NERVOUS SYSTEM DAMAGE, ALSO, KIDNEY AND LIVER DAMAGE.
Effects of Overexposure:SKIN IRRITANT & UPPER RESPIRATORY SYSTEM,
LIGHT-HEADEDNESS, STAGGERING GAIT, POSSIBLE NAUSEA.

=====
===== First Aid Measures =====

First Aid:INHALE: REMOVE TO FRESH AIR; EYES: FLUSH WITH WATER FOR AT
LEAST 15 MINUTES; SKIN: WASH WITH SOAP AND WATER; INGEST: CALL
PHYSICIAN. DO NOT INDUCE VOMITING.

=====
===== Fire Fighting Measures =====

Flash Point:NONE
Fire Fighting Procedures:WATER MAY BE INEFFECTIVE. WATER COOL
CONTAINERS.
Unusual Fire/Explosion Hazard:KEEP AT ROOM TEMP AS EXPOSURE TO DIRECT
SUNLIGHT OR OTHER HEAT MAY CAUSE BURSTING.

=====
===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA-ESPECIALLY LOW PLACES WHERE
VAPORS WILL COLLECT. AVOID BREATHING OF VORS AND REMOVE WITH INERT
ABSORBENT.

=====
===== Handling and Storage =====

=====

Handling and Storage Precautions:DON'T STORE >120F. KEEP AT ROOM TEMP
AS EXPOSURE TO DIRECT SUNLIGHT OR HEAT MAY CAUSE BURSTING
Other Precautions:KEEP AWAY FROM CHILDREN. DON'T PUNCTURE OR
INCINERATE. DON'T SPRAY NEAR FIRE OR OPEN FLAME.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:AVOID BREATHING OF VAPOR OR SPRAY MIST.
Ventilation:PROVIDE LOCAL EXHAUST VENTILATION TO KEEP