

DEXTER CORPORATION,HYSOL DIVISION -- EA-934 PART A -- 8040-00-810-5414

===== Product Identification =====

Product ID:EA-934 PART A

MSDS Date:01/01/1987

FSC:8040

NIIN:00-810-5414

Kit Part:Y

MSDS Number: BFQJC

=== Responsible Party ===

Company Name:DEXTER CORPORATION,HYSOL DIVISION

Emergency Phone Num:415 687 4201

CAGE:79436

=== Contractor Identification ===

Company Name:DEXTER CORP DEXTER ELECTRON

IC MATERIALS

Address:15051 E DON JULIAN RD

Box:City:INDUSTRY

State:CA

ZIP:91746-1282

Country:US

Phone:626-968-6511

CAGE:79436

Company Name:DEXTER CORPORATION ADHESIVE & COATING SYSTEMS

Address:2850 WILLOW PASS ROAD

Box:312

City:BAY POINT

State:CA

ZIP:94565-3299

Country:US

Phone:202-483-7616

CAGE:33564

===== Composition/Information on Ingredients =====

Ingred Name:ASBESTOS, AMOSITE (OSHA PEL FROM 29CFR 1910.1001)

CAS:12172-73-5

RTECS #:CI6477000

Fraction by Wt: 14%.

OSHA PEL:

0.2 FIBERS/CC

ACGIH TLV:0.5 FIBER/CC,A1;8990

Ingred Name:NON-HAZARDOUS MATERIALS(TYPE NOT SPECIFIED)

Fraction by Wt: 86%.

=====  
===== Hazards Identification =====

Effects of Overexposure:SKIN: MAY IRRITATE & POSSIBLE ALLERGIC REACTION;PROLONGED & REPEATED CONTACT MAY CAUSE SENSITIZATN

=====  
===== First Aid Measures =====

First Aid:EYES/SKIN:FLUSH W/PLENTY OF WATER;WASH SKIN THOROUGHLY W/SOAP & WATER;RUBBING ALCOHOL OR HAND CLEANER. DO NOT USE SOLVENTS;REMOVE SOILED CLOTHING & WASH BEFORE REUSE. IF IRRITATION PERSISTS OR INCREAS E, SEE A PHYSICIAN.

=====  
===== Fire Fighting Measures =====

Flash Point:>200F/>93.3

Extinguishing Media:DRY CHEMICALS,WATER SPRAY OR FOG,FOAM

Fire Fighting Procedures:WEAR SELF-CONTND.BRTHNG APPART(SCBA)FIRE FIGHTNG CONF.SPACE

Unusual Fire/Explosion Hazard:DENSE SMOKE & TOXIC GASES MAY BE LIBERATED FROM HEAT OF FIRE.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE CLOTHING,GLOVES, & SAFETY GLASSES;SCRAPE UP REMAINING RESIDUE W/SOLVENTS,OBSERVING SOLVENT FLAMMABILITY CAUTIONS, OR USE DETERGENT

=====  
===== Handling and Storage =====

Handling and Storage Precautions:KEEP PRODUCT COOL IAW LABEL INSTRUCTIONS; DONOT HEAT MIXED ADHESIVE ABOVE 125F UNLESS CURING SURFACES TO BE BONDED; OBSERVE CAUTIONS FOR HEAT BUILD-UP

Other Precautio

ns:FOLLOW RECOMMENDED CURING SCHEDULE;DO NOT HEAT MIXED  
ADHESIVE (>125F); FAILURE TO OBSERVE CAUTIONS MAY RESULT IN  
EXCESSIVE HEAT BUILD-UP WITH RELEASE OF TOXIC GASES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPRVD MASK FOR TOXIC DUSTS WHEN CURED  
PRODUCT DRY SANDED,ETC.

Ventilation:LOCAL EXHAUST: RECOMMENDED WHEN SANDING CURED  
PRODUCT;MECHAN

Protective Gloves:IMPERVIOUS TYPE

Eye Protection:SAFETY GLASSES/GOGGLES

Other Pr

otective Equipment:AS NEEDED TO PROTECT SKIN & CLOTHING

Supplemental Safety and Health

MSDS DATED: 4/85; SPEC: TY 1, CL 3;. KEY1:N1.

===== Physical/Chemical Properties =====

HCC:B2

Boiling Pt:B.P. Text:DECOMPOSES

Vapor Pres: