View NSN Online: https://aerobasegroup.com/nsn/8040-00-810-5414

Product ID:EA-934 PART B MSDS Date:01/01/1987 FSC:8040 NIIN:00-810-5414 Kit Part:Y MSDS Number: BFQJD === Responsible Party === Company Name: DEXTER CORPORATION, HYSOL DIVISION Address:2850 WILLOW PASS ROAD Box:312 City:PITTSBURG State:CA ZIP:94565-3237 Country:US Info Phone Num:415-687-4201 Em ergency Phone Num:415-687-4201 CAGE:79436 === Contractor Identification === Company Name: DEXTER CORP DEXTER ELECTRONIC MATERIALS Address:15051 E DON JULIAN RD Box:City:INDUSTRY State:CA ZIP:91746-1282 Country:US Phone:626-968-6511 CAGE:79436 **Company Name: DEXTER CORPORATION ADHESIVE & COATING SYSTEMS** Address:2850 WILLOW PASS ROAD Box:312 **City:BAY POINT** State:CA ZIP:94565-3299 Country:US Phone:202-483-7616 CAGE:33564

Ingred Nam

e:DIETHYLENE TRIAMINE
CAS:111-40-0
RTECS #:IE1225000
Fraction by Wt: 13%
OSHA PEL:1 PPM
ACGIH TLV:S, 1 PPM; 9192

Ingred Name:NON-HAZARDOUS MATERIALS(TYPE NOT SPECIFIED) Fraction by Wt: 87%

Effects of Overexposure:SKIN/EYES: CORROSIVE & CAN CAUSE CHEM. BURNS; **INHAL: IRRITATING & CHEST DISCOMFORT & BRONCHIAL SYMPTM**

First Aid: EYES/SKIN: FLUSH W/PLENTY OF WATER; WASH SKIN THOROUGHLY W/SOAP & WATER; FOR EYES, FLUSH IMMEDIATELY FOR 15 MINUTES & GET MEDICAL AID. INGESTION: GIVE WATER OR MILK IF SWALLOWED, DO NOT INDUCE VOMITIN G. GET MEDICAL AID.

Flash Point:>200F/>93.3C Extinguishing Media: DRY CHEMICALS, WATER SPRAY OR FOG, FOAM Fire Fighting Procedures:WEAR SELF-CONTND.BRTHG APPART(SCBA)FIRE FIGHTNG CONF.SPACE Unusual Fire/Explosion Hazard: DENSE SMOKE & TOXIC GAS ES MAY BE LIBERATED FROM HEAT OF FIRE.

Spill Release Procedures: WEAR PROTECTIVE CLOTHING, GLOVES, & SAFETY GLASSES; SCRAPE UP & TRANSFER TO METAL CONTAINER-WIPE UP REMAINING RESIDUE W/SOLVENTS, OBSERVING SOLVENT FLAMMABILITY CAUTIONS, OR USE DETERGENT.

Handling and Storage Precautions: KEEP PRODUCT COOL IAW LABEL INSTRUCTIONS; DONOT HEAT MIX

ED ADHESIVE ABOVE 125F UNLESS CURING SURFACES TO BE BONDED; OBSERVE CAUTIONS OR HEAT BUILD-UP Other Precautions:FOLLOW RECOMMENDED CURING SCHEDULE; DO NOT HEAT MIXED ADHESIVE (>125F); FAILURE TO OBSERVE CAUTIONS MAY RESULT IN EXCESSIVE HEAT BUILD-UP WITH RELEASE OF TOXIC GASES.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NIOSH APPRVD MASK FOR TOXIC DUSTS WHEN CURED PRODUCT DRY SANDED,ETC. Ventilation:LOCAL EXHAUST: RECOMMENDED WHEN SANDING CURED PRODUCT;MECHAN Protective Gloves:IMPERVIOUS TYPE Eye Protection:SAFETY GLASSES/GOGGLES Other Protective Equipment:AS NEEDED TO PROTECT SKIN & CLOTHING Supplemental Safety and Health MSDS DATED: 4/85; SPEC: TY 1,CL 3;. KEY1:B2.

HCC:B2 Boiling Pt:B.P. Text:DECOMPOSES Vapor Pres: