

ATLAS PAINT & VARNISH CO -- TT-E-529C, GREEN 24260 PAINT -- 8010-00-811-1922

=====  
Product Identification  
=====

Product ID:TT-E-529C, GREEN 24260 PAINT

MSDS Date:01/01/1987

FSC:8010

NIIN:00-811-1922

MSDS Number: BFQKJ

=== Responsible Party ===

Company Name:ATLAS PAINT & VARNISH CO

Emergency Phone Num:201-373-3300

CAGE:KO008

=== Contractor Identification ===

Company Name:ATLAS PAINT & VARNISH CO.

CAGE:KO008

Company Name:ATLAS PAINT AND VARNISH CO

CAGE:84239

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PIGMENTS (SEE SUPPLIMENTAL DATA FOR SPECIFIC TYPES)

Fraction by Wt: 38.0%

ACGIH TLV:0.15 MG/CUM-MFG

Ingred Name:ALKYD RESIN

Fraction by Wt: 25.0%

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 36.0%

OSHA PEL:100 PPM

Ingred Name:LEAD COBALT DRIERS (OSHA PEL FROM 29CFR 1910.1025)

Fraction by Wt: 1.0%

O

SHA PEL:0.05 MG/M3 (PB)

ACGIH TLV:0.15 MG/M3(PB); 8990

=====  
Hazards Identification  
=====

Effects of Overexposure:INHALATION: (HIGH CONC) MAY CAUSE MILD  
DEPRESSION & LOSS OF CONSCIOUSNESS.

=====  
First Aid Measures  
=====

First Aid:REMOVE FROM EXPOSURE & CALL PHYSICIAN. FLUSH AFFECTED PARTS  
WITH WATER.

=====  
Fire Fighting Measures  
=====

Flash Point:108F TCC

Lower Limits:0.09

Uppe

r Limits:6.0

Extinguishing Media:CO\*2, FOAM, DRY CHEMICAL, WATER FOG

Fire Fighting Procedures:USE AIR-SUPPLIED RESCUE EQUIP - COOL EXPOSED CONTAINER.

Unusual Fire/Explosion Hazard:USUAL HAZARD POTENTIAL BASED ON FLASH POINT

===== Accidental Release Measures =====

Spill Release Procedures:WIPE UP IMMEDIATELY & DISCARD ABSORBENTS SAFELY. REMOVE OPEN IGNITION. DIKE LG SPILLS & PUMP INTO WASTE TANK. KEEP VENTILATED & AVOID PROLONGED BREATHING OF VAPORS.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID OPEN FLAMES - SPARKS & EXCESSIVE HEAT - VENTILATE AREA.

Other Precautions:READ LABEL REGARDING TOXICITY & APPLICATION. DOT: COMBUSTIBLE LIQUID.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RECOMMENDED - NIOSH APPROVED RESP PROT FOR PART EXP OF CONCERN

Ventilation:LOCAL: MOST DESIRABLE

Protective Gloves:RECOMMENDED

Eye Protection:

RECOMMENDED

Other Protective Equipment:CONVENTIONAL CLOTHING FOR PAINTING

Supplemental Safety and Health

PIGMENTS: TIO\*2, PHTHALO GREEN, YELLOW OXIDE & BLACK SILICATE. MFG SUGGESTS A TLV OF 200 PPM PER 8 HR WORK DAY.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:317-388F

Vapor Pres:5.

Vapor Density:4.80

Spec Gravity:1.0500

Evaporation Rate & Reference:0.09 (BUAC)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:MINERAL SPIRITS ODOR -

THIN GREEN PAINT

Percent Volatiles by Volume:54.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXYGEN & STRONG OXIDENTS

Stability Condition to Avoid:OPEN FLAME

Hazardous Decomposition Products:CO & CO\*2 WHEN COMBUSTED

===== Disposal Considerations =====

Waste Disposal Methods:SPECIAL HAZARDOUS WASTE CARRIER. EPA REGULATED -  
STATE OR FEDERAL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.