

PYROIL COMPANY,DIV.OF CHAMPION LABS INC. -- STARTING FLUID -- 6850-00-823-7861

=====
Product Identification
=====

Product ID:STARTING FLUID

MSDS Date:01/01/1987

FSC:6850

NIIN:00-823-7861

MSDS Number: BFQXT

=== Responsible Party ===

Company Name:PYROIL COMPANY,DIV.OF CHAMPION LABS INC.

Address:4TH AND WALNUT ST

City:ALBION

State:IL

ZIP:62806

Country:US

Emergency Phone Num:NONE KNOWN

CAGE:MO041

===

Contractor Identification ===

Company Name:CHAMPION LABORATORIES INC

Address:4TH AND WALNUT ST

Box:City:ALBION

State:IL

ZIP:62806

Country:US

Phone:618-445-6011

CAGE:1U777

Company Name:PYROIL COMPANY,DIV.OF CHAMPION LABS INC.

Address:4TH AND WALNUT ST

Box:City:ALBION

State:IL

ZIP:62806

Country:US

CAGE:MO041

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHYL ETHER (SARA III)

CAS:60-29-7

RTECS #:KI5775000

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400PPM/500STEL; 91

92

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:PETROLEUM DISTILLATE

ACGIH TLV:500 PPM (MFR)

=====
===== Hazards Identification =====

Effects of Overexposure:EYES:IRRITATION,REDNESS,TEARING,BLURRED VISION;SKIN:IRRIT,DEFAT,DERMATITIS;INHAL:DROWSINESS,CNS DEP-

=====
===== First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H*2O FOR 15 MIN;INGEST:RINSE MOUTH;

GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE.

=====
===== Fire Fighting Measures =====

Flash Point:-36F/-38C (TCC)

Lower Limits:1.46

Upper Limits:18.6

Extinguishing Media:CO*2,DRY CHEMICAL,FOAM

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN CONFINED AREA.

Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND TO A DISTANT IGNITION SOURCE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;REMOVE ALL IGNITION SOURCES;RECOVER FREE LIQUID;ADD SOLID ABSORBENT TO SPILL AREA AND RECOVER FOR PROPER DISPOSAL.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL VENTILATED AREA.KEEP AWAY FROM HEAT,OPEN FLAMES.

Other Precautions:AVOID CONTACT WITH EYES AND SKIN;DO NOT BREATHE VAPORS.

=====
===== Exposu

re Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR
ORG.VAPORS/MIST IF ABOVE TLV.

Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN