View NSN Online: https://aerobasegroup.com/nsn/6850-00-823-7861

PYROIL COMPANY DOV OF CHAMPION LABORATORIES, INC -- STARTING FLUID

6850-00-823-7861

============= Product Identification ===============

Product ID:STARTING FLUID

MSDS Date:01/01/1985

FSC:6850

NIIN:00-823-7861

MSDS Number: BFQXW === Responsible Party ===

Company Name: PYROIL COMPANY DOV OF CHAMPION LABORATORIES, INC

Address:WALNUT ST

Box:40-T City:ALBION State:IL ZIP:62806

Country:US CAGE:MO042

=== Contractor Id entification ===

Company Name: PYROIL CO INC

Address:WALNUT ST

Box:40-T City:ALBION

State:IL ZIP:62806 Country:US CAGE:98727

Company Name: PYROIL COMPANY DOV OF CHAMPION LABORATORIES, INC

Address:WALNUT ST

Box:40-T City:ALBION State:IL ZIP:62806 Country:US

CAGE:MO042

======= Composition/Information on Ingredients ========

Ingred Name: ETHYL ETHER (SARA III)

CAS:60-29-7

RTECS #:KI5775000 Fraction by Wt: 60%

OSHA PEL:400 PPM/500 STEL ACGIH TLV:400PPM/500STEL; 9192

EPA Rpt Qty:100 LBS

Ingred Name:N-HEPTANE CAS:142-82-5 RTECS #:MI7700000 Fraction by Wt: 40% OSHA PEL:500 PPM/500 STEL ACGIH TLV:400 PPM/500STEL;9293
======================================
Effects of Overexposure:ETHER IS CENTRAL NERVOUS SYSTEM DEPRESS ANT.CAN PRODUCE INTOXICATION,DROWINESS,STUPOR.
======================================
First Aid:ANDREMOVE VICTIM TO FRESH AIR. IF CONTACT WITH EYES OCCURS,FLUSH WITH WATER FO R 15 MINUTES.IF SWALLOWED DO NOT INDUCE VOMITING.
======================================
Flash Point:-41 F TCC Lower Limits:1.46 Upper Limits:18.6 Extinguishing Media:FOAM,CO2 DRY CHEMICAL Unusual Fire/Explosion Hazard:EXTREMELY FLAMMABLE
========= Accidental Release Measures ============
Spill Release Procedures:REMOVER FREE LIQUID.USE SOLID ABSORBENT AND PROTECT FROM HEAT, SPARKS, OR OPEN FLAME.
======================================
Handling and Storage Precautions:HANDLE AS EXTREMELY FLAMMABLE.
====== Exposure Controls/Personal Protection ========
Ventilation:AS REQUIRED Protective Gloves:APPROVED HAND Eye Protection:USE APPROVED EYE PROTECTI Supplemental Safety and Health SPEC: II TYPE;EFFECTS FO EXPOSURE:ETHER IS A DEPRESSANT OF THE CENTRAL NERVOUS SYSTEM & CAN PRODUCE INTOXICATION,DROWSINESS,STUPOR,UNCONSCIOUSNESS;HEPTANE IS IRRITNT TO RESPIRATORY TRACT.

DOT Rpt Qty:100 LBS

======= Physical/Chemical Properties ===========	
HCC:V3 Boiling Pt:B.P. Text:163 Vapor Pres:200 Vapor Density:3.09 Spec Gravity:0.695 Evaporation Rate & Deference:1.6 Solubility in Water:INSOL Appearance and Odor:A CLEAR VOLATILE LIQUID Percent Volatiles by Volume:99.3	

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:KEEP AWAY FROM HEAT,SPARKS OR FLAME.

Disclai

mer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.