

PRODUCTS/TECHNIQUES,INC. -- ANTIFOULING PPAINT PT-199 -- 8010-00-823-7911
===== Product Identification =====

Product ID:ANTIFOULING PPAINT PT-199
MSDS Date:01/01/1987
FSC:8010
NIIN:00-823-7911
MSDS Number: BFQYG
=== Responsible Party ===
Company Name:PRODUCTS/TECHNIQUES,INC.
Emergency Phone Num:213-770-3600
CAGE:06341
=== Contractor Identification ===
Company Name:PRODUCTS/TECHNIQUES INC
Address
s:3271 S RIVERSIDE AVE
Box:City:RIALTO
State:CA
ZIP:92376
Country:US
Phone:909-877-3951
CAGE:06341

===== Composition/Information on Ingredients =====

Ingred Name:CUPROUS OXIDE
Fraction by Wt: 53.0%
ACGIH TLV:1.0 MG/CUM

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 42.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM/150STEL;9394
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards

Identification =====

Effects of Overexposure:SKIN IRRITATION,EYE IRRITATION,ANESTHESIA,HEADACHE AND NAUSEA, DIZZINESS

===== First Aid Measures =====

First Aid:SKIN-USE SOAP AND WATER.EYES-INCASE OF EYE CONTACT FLUSH EYES WITH WATER, REMOVE VICTIM TO FRESH AIR AND RESTORE BREATHING IF REQUIRED.

===== Fire Fighting Measures =====

Flash Point:80 F, 27 C TCC

Lower Limits:1.0

Upper Limits:7.0

Ext

inguishing Media:FOAM,CO*2 STEAM,WATER-FOG,DRY CHEMICAL

Fire Fighting Procedures:DO NOT USE WATER, EXCLUDE AIR

Unusual Fire/Explosion Hazard:VAPOR FORMS EXPOOSIVE MIXTURES WITH AIR BETWEEN VEL AND LEL.

===== Accidental Release Measures =====

Spill Release Procedures:AVOID OPEN FLAMES OR SPARK SOURCE-PROVIDE ADEQUATE VENTILATION,ABSORB WITH SWEEPING COMPOUND

===== Handling and Storage =====

Handling and Storage Precautions

:AVOID OPEN FLAMES AND SPARKS,AVOID

SPLASH FILLING.STORE IN SEALED CONTAINERS.KEEP CONTAINERS CLOSED TO PREVENT MOISTURE ABSORPTION.

Other Precautions:AVOID SKIN & EYE CONTACT, WASH IMMEDIATELY AFTER CONTACT WITH SOAP & WATER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:ORGANIC MASK

Ventilation:LOCAL EXHAUST RECOM. APPROVED CLASS D FOR MECHANICAL

Protective Gloves:NOT REQUIRED

Eye Protection:SAFETY GLASSES DESIRED

Supplemental Safety a

nd Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:281-294 F

Vapor Pres:6

Vapor Density:3.7

Spec Gravity:1.62

Evaporation Rate & Reference:0.59 BUTYL ACETATE

Percent Volatiles by Volume:60.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:EVA

PORATE OR FLUSH WITH WATER TO OPEN WELL

VENTILATE D AREA-USE OIL SEWER IF AVAILABLE-REMOVE TO
INCINERATOR,FOLLOW LOCAL EPA REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.