

NORRIS PAINT & VARNISH CO.,INC -- EXTERIOR LATEX PAINT -- 8010-00-823-7962

=====  
Product Identification  
=====

Product ID:EXTERIOR LATEX PAINT

MSDS Date:01/01/1987

FSC:8010

NIIN:00-823-7962

MSDS Number: BFQZP

=== Responsible Party ===

Company Name:NORRIS PAINT & VARNISH CO.,INC

Emergency Phone Num:503-364-277/8060

CAGE:GO781

=== Contractor Identification ===

Company Name:NORRIS PAINT & VARNISH CO

Box:2023

CAGE:GO781

Company Name:NORRIS PAINT CO., DIV WHITTAKER COATINGS

Address:1675 COMMERCIAL ST NE

Box:2023

City:SALEM

State:OR

ZIP:97308

Country:US

Phone:503-364-2277

CAGE:33148

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PIGMENT

Fraction by Wt: 37.0%

Ingred Name:VEHICLE

Fraction by Wt: 19.0%

Ingred Name:ETHYLENE GLYCOL (SARA III)

CAS:107-21-1

RTECS #:KW2975000

Fraction by Wt: 1.6%

OSHA PEL:C 50 PPM

ACGIH TLV:C 50 PPM,VAPOR; 9192

EPA Rpt Qty:1 LB

D

OT Rpt Qty:1 LB

=====  
Hazards Identification  
=====

Effects of Overexposure:INHAL OF VAPORS/SPRAY-SHORTNESS OF BREATH,NAUSEA WHEN INGESTED. VAPOR IRRITATES EYES

=====  
First Aid Measures  
=====

First Aid:INGESTED:INDUCE VOMIT,GET DR. EYE:FLUSH W/WATER FOR 15 MIN.AND GET DR. INHAL:REMOVE TO FRESH AIR.

=====  
Fire Fighting Measures  
=====

Flash Point:NONE

=====  
Accident  
al Release Measures  
=====

Spill Release Procedures:ABSORB AND FLUSH WITH LARGE AMTS. OF WATER.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE UPRIGHT,DO NOT FREEZE.KEEP CONTAINER CLOSED WHEN NOT IN USE.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:PAINTERS MASK FOR SPRAY APPKICATION  
Ventilation:LOCAL EXHAUST FOR OPEN AIR APPLICATIO ONLY  
Other Protective Equipment:EYE B  
ATH AND SAFETY SHOWER  
Supplemental Safety and Health

=====  
Physical/Chemical Properties  
=====

HCC:N1  
Boiling Pt:B.P. Text:212 F, 100C  
Vapor Pres:24  
Spec Gravity:1.38  
Solubility in Water:COMPLETE  
Appearance and Odor:APAQUE LIQUID WITH SLIGHT AMMONIA ODOR  
Percent Volatiles by Volume:60.0

=====  
Stability and Reactivity Data  
=====

Stability Indicator/Materials to Avoid:YES  
OIL AND OILBASED MATERIAL,PETROLEUM DISTILLATES,STRONG ACIDS  
Stability

Condition to Avoid:EXTREME HEAT,OVER 200 F.

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:FLUSH DOWN DRAIN OR DISPOSE OF IN LANDFILL  
ACCORDING TO LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants th  
is information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.