

EASTMAN KODAK COMPANY -- 195 6507,KODAFLAT CLEAR SOLUTION -- 6750-00-824-9075
===== Product Identification =====

Product ID:195 6507,KODAFLAT CLEAR SOLUTION

MSDS Date:01/01/1985

FSC:6750

NIIN:00-824-9075

MSDS Number: BFRGY

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-722-5151

Emergency Phone N

um:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

===== Composition/Information on Ingredients =====

Ingred Name:ETHYL ACETATE (SARA III)

CAS:141-78-6

RTECS #:AH5425000

Fraction by Wt: 55%

OSHA PEL:400 PPM

ACGIH TLV:400 PPM; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ETHY

L ALCOHOL (ETHANOL)
CAS:64-17-5
RTECS #:KQ6300000
Fraction by Wt: 15%
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM; 9192

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 15%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:TRIORTHOCRESYL PHOSPHATE
CAS:78-30-8
RTECS #:TD0350000
Fraction by Wt: 15%
OSHA PEL:S, 0.1 MG/M3
ACGIH TLV:S, 0.1 MG/M3; 9192

=====
===== Hazards Identification =====

Ef
fects of Overexposure:VAPOR IRRITATS MUCOUSA.CAN DAMAGE
LIVER,KIDNEY,LUNG,HEART.REPEATED/PROLONG CONTACT DEFATS,IRRITATS.

=====
===== First Aid Measures =====

First Aid:IN CASE OF CONTACT,FLUSH AREA WITH PLENTY OF WATER.IF INHALED
REMOVE TO FRESH AIR.GET PROMPT MEDICAL ATTENTION OF SYMPTOMS
PERSIST.

=====
===== Fire Fighting Measures =====

Flash Point:14F/-16C SCC
Extinguishing Media:CARBON DIOXIDE,DRY CHEMICAL
Fire Figh

ting Procedures:WEAR SELF-CONTAINED BREATHING APP;USE WATER TO COOL CONTAIN

Unusual Fire/Explosion Hazard:SOLUTION CONTAINS CELLULOSE NITRATE

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES.EVACUATE UNPROTECTED PERSONS.FLUSH TO SEWER WITH PLENTY OF WATER IF FEDERAL,STATE AND LOCAL EFFLUENT LAWS PERMIT.

===== Handling and Storage =====

Handling and Storage Precautions:STORE I N COOL,DRY,LOW FIRE RISK AREA.KEEP CONTAINERS CLOSED.PROTECT FROM PHYSICAL DAMAGE.AVOID IGNITION SOURCES.

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED ORGANIC VAPOR RESPIRATOR FOR EMERGENCY SITUATIONS

Ventilation:MECHANICAL(GENERAL) RECOMMENDED.LOCAL EXHAUST TO CONTROL TLV

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GOGGLES

Other Protective Equipment:NONE

Supplemental Safety and Health

FLASHPOI

NT:12F/-11C TOC(PER MFR 6-1-83)

===== Physical/Chemical Properties =====

HCC:F2

Vapor Pres:UNK

Vapor Density:UNK

Spec Gravity:0.918

Solubility in Water:SLIGHT

Appearance and Odor:WATER WHITE LIQUID,PLEASANT FRUITY ODOR.

Percent Volatiles by Volume:82

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

MFR STATES NONE

Stability Condition to Avoid:OPEN FLAME

Hazardous Decomposition Products:IF COMBUSTED:CARB

ON DIOXIDE,CARBON
MONOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE IN ACCORDANCE WITH FEDERAL,STATE AND
LOCAL EFFLUENT LAWS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability
y for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.