View NSN Online: https://aerobasegroup.com/nsn/6810-00-824-9090

MALLINCKRODT INC., SCIENCE PRODUCTS DIVISION -- BORIC ACID -- 6810-00-824-9090

Product ID:BORIC ACID MSDS Date:01/01/1987 FSC:6810 NIIN:00-824-9090 MSDS Number: BFRGZ === Responsible Party === Company Name: MALLINCKRODT INC., SCIENCE PRODUCTS DIVISION Emergency Phone Num:(314)982-5000 CAGE:62910 === Contractor Identification === Company Name: MALLINCKRODT SPECIALTY CHEMICALS CO Address:222 RED SCHOOL LANE Box:City:PHILLIPSBURG State:NJ ZIP:08865 Country:US Phone:908-859-2151 CAGE:62910

Ingred Name:BORIC ACID;ORTHO-BORIC ACID;BORACIC ACID; CAS #10043-35-3 CAS:10043-35-3 RTECS #:ED4550000 Fraction by Wt: >99% ACGIH TLV:NOT KNOWN

Effects of Overexposure:INH:MAY IRRIT MUC MEMB OF RESP TRACT;ING:SYMPTMS SIMILAR TO INH ;SKIN/EYES:MAY CAUSE IRRITATION.

First Aid:SKIN:WASH W.SOAP & H\*20 EYES:FLUSH W. H\*20. INGESTED:GIVE 2 GLASSES H\*20; INDUCE VOMITING.CALL A PHYSICIAN. INHALE:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. KEEP WARM & QUIET. REMOVE CONTAMINATED CLOTHING. IF UNCONS DO NOT TAKE ANYTHING BY MOUTH.

Flash Point:NONE Extinguishing Media:EXTINQUISH W.

AGENT SUITABLE FOR SURROUNDING FIRE. Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*20 SPRAY TO COOL CONTR.
Unusual Fire/Explosion Hazard: A MIXTURE OF POTASSIUM & BORIC ACID MAY EXPLODE ON IMPACT.
======================================
Spill Release Procedures:CLEAN-UP PERSONNEL NEED PROTECTION FROM INHALATION OF DUST.COLLECT SOLID SPILLS & PLACE IN APPROPRIATE CONTAINERS FOR DISPOSAL.LIQUID(SOLUTIONS)SPILLS CAN BE ABSORBED W/INERT SOLID.RE SIDUE TRACES CAN BE FLUSHED TO SEWER WITH HIGH DILUTION.
======================================
<ul> <li>Handling and Storage Precautions: KEEP IN TIGHTLY CLOSED CONTNRS AT COOL, DRY, VENTILATED PLACE.PROTECT AGAINST PHY DAMAGE; CARBON STEEL OR ALUMNM CONTNRS ARE SUITABLE FOR STORAGE.</li> <li>Other Precautions: AVOID BREATHING DUST. USE W/ADEQUATE VENTILATION. KEEP CONTAINRS CLOSED. WASH THOROUGHLY AFTER HANDLING. AVOID SKIN, EYES &amp; CLOTHING CONTACT; STAINLESS STEEL IS NE EDED FOR MOIST CONDITIONS.</li> </ul>
======================================
Respiratory Protection:SUPPLIED AIR RESPIR/SCBA; ESCAPE: GAS MASK Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV. Protective Gloves:IMPERVIOUS
Eye Protection:GOGGLES/FACE SHIELD Other Protective Equipment:FULL PROTECTIVE CLOTHING,SAFETY SHOWER,EYE WASH STATION
Supplemental Safety and Health MSDS FROM MFR DATED:28 FEB 85 CONFORMS TO OSHA HAZ COMM STD.
======================================
HCC:N1 Boiling Pt:B.P. Text:DECOPOSES Spec Gravity:1.43 Solubility in Water:COMPLETE
Appearance and Odor:COLORLESS CRYSTALS,NO APPARENT ODOR
======================================
Stability Indicator/Materials to Avoid YES

Stability Indicator/Materials to Avoid:YES POTASSIUM,ACETIC ANHYDRIDE Stability Condition to Avoid:MOISTURE Hazardous Decomposition Products:BORON OXIDE WHEN HEATED TO DECOMPOSITION

## posal Methods:RECLAIM DRY MATERIAL FOR SALVAGE OR REUSE. UNSALVAGEABLE WASTE MAY BE SENT TO A RCRA APPROVED LANDFILL.ENSURE COMPLIANCE WITH LOCAL,STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use.

Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.