

ELECTROFILM -- LUBE-LOK 5306 (CONCENTRATE) -- 9150-00-834-5608

===== Product Identification =====

Product ID:LUBE-LOK 5306 (CONCENTRATE)

MSDS Date:01/01/1987

FSC:9150

NIIN:00-834-5608

MSDS Number: BFRSP

=== Responsible Party ===

Company Name:ELECTROFILM

Address:7116 LAUREL CANYON BLVD

City:NORTH HOLLYWOOD

State:CA

ZIP:91605

Info Phone Num:213-875-1000

Emergency Phone Num:213-875-1000

CAGE:MO076

=

== Contractor Identification ==

Company Name:ELECTROFILM

Address:7116 LAUREL CANYON BLVD

Box:City:NORTH HOLLYWOOD

State:CA

ZIP:91605

Phone:213-875-1000

CAGE:MO076

Company Name:ELECTROFILM MFG CO

Address:27727 AVE SCOTT

Box:55669

City:VALENCIA

State:CA

ZIP:91355

Country:US

Phone:805-257-2242

CAGE:85932

===== Composition/Information on Ingredients =====

Ingred Name:MOLYBDENUM DISULFIDE

CAS:1317-33-5

RTECS #:QA4697000

OSHA PEL:10 MG/M3 TDUST (MO)

ACGIH TLV:10 MG/M3 (MO); 8990

Ingred Name:LEAD PHOSPHITE
CAS:1344-40-7
RTECS #:OG2880000

Ingred Name:ANTIMONY TRIOXIDE (SARA III)
CAS:1309-64-4
RTECS #:CC5650000
OSHA PEL:0.5 MG/M3 (SB)
ACGIH TLV:0.5 MG SB/M3; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:PHENOLIC RESIN
Fraction by Wt: 10.6%

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)
CAS:108-10-1
RTECS
#:SA9275000
OSHA PEL:100 PPM/75 STEL
ACGIH TLV:50 PPM/75 STEL; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:LIQUID IS MODERATELY IRRITATING TO
SKIN A

ND EYES.

Explanation of Carcinogenicity:NOT LISTED

Effects of Overexposure:HEADACHE, NAUSEA, DIZZINESS, ETC. LIQUID
MODERATELY IRRITATING TO SKIN AND EYES.

Medical Cond Aggravated by Exposure:SKIN DISORDERS, PULMONARY DISORDERS

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE VICTIM AND RESTORE BREATHING IF REQUIRED.
SKIN: REMOVE WITH SOAP & WATER. EYES: FLUSH EYES WITH WATER FOR 15
MINUTES. GET MEDICAL ATTENTION.

=====
=== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:34F,1C

Lower Limits:1.0

Upper Limits:7.0

Extinguishing Media:FOAM,CO2, STEAM, WATER-FOG OR DRY CHEMICAL

Fire Fighting Procedures:EXCLUDE AIR, COOL EXPOSED CONTAINERS WITH
WATER.

Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

=====
===== Accidental Release Measures =====

Spill Release Procedures:AVOID OPEN FLAMES, SPARKS OR IGNITION SOURCES.
VENTILATE AREA. ABSORB

MATERIAL AND PLACE IN DISPOSAL CONTAINER.

Neutralizing Agent:NONE

=====
===== Handling and Storage =====

Handling and Storage Precautions:AVOID OPEN FLAMES AND SPARK SOURCES,
AVOID SPLASH FILLING. PROVIDE ADEQUATE VENTILATION. AVOID EXCESSIVE
HEAT. KEEP CONTAINER CLOSED WHEN NOT IN USE.

Other Precautions:NONE

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPROVED ORGANIC CANISTER MASK OR AIR
MASK.

Ven

tilation:LOCAL EXHAUST IS DESIRABLE, MECHANICAL(GENERAL) REQUIRED WITH CLASS "D" EXPLOSION PROFF MOTOR AND SWITCHES.

Protective Gloves:NORMALLY NOT REQUIRED

Eye Protection:CHEMICAL SPLASH GOGGLES AND/OR SHIELD

Other Protective Equipment:LONG SLEEVED WORK CLOTHING. EYE WASH STATION.

Work Hygienic Practices:LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

NONE.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:132F,

55.5C

Vapor Pres:24

Vapor Density:2.9

Spec Gravity:1.06

Evaporation Rate & Reference:1.6 (N.BUTYL ACETATE=1)

Solubility in Water:NEGIGIBLE

Appearance and Odor:GRAY PAINT LIKE MATERIAL. AROMATIC ODOR LIKE BENZENE.

Percent Volatiles by Volume:86

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING MATERIALS.

Hazardous Decomposition Products:CO, CO2 WHEN BURNED.

===== Disposal Considerations =====

Waste Disposal Methods:WIPE UP WITH ABSORBENT MATERIAL OR FLUSH WITH WATER TO OPEN, WELL VENTILATED AREA. USE OIL SEWER IF AVALIABLE. REMOVE TO CONTAINER. FOLLOW APPLICABLE FEDERAL, STATE OR LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information t

o be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.