

SEYMOUR OF SYCAMORE, INC -- GRAY LACQUER, VINYL TOLUENE ALKYD RESIN --  
8010-00-835-7215

=====  
Product Identification  
=====

Product ID:GRAY LACQUER, VINYL TOLUENE ALKYD RESIN

MSDS Date:01/26/1987

FSC:8010

NIIN:00-835-7215

MSDS Number: BFRVP

=== Responsible Party ===

Company Name:SEYMOUR OF SYCAMORE, INC

Address:917 CROSBY AVE

City:SYCAMORE

State:IL

ZIP:60178

Info Phone Num:(815) 895-9101

Emergency

Phone Num:(815) 895-9101

CAGE:59581

=== Contractor Identification ===

Company Name:SEYMOUR OF SYCAMORE

Address:917 CROSBY AVE.

Box:City:SYCAMORE

State:IL

ZIP:60178-1343

Country:US

Phone:815-895-9101/800-255-3924

CAGE:59581

=====  
Composition/Information on Ingredients  
=====

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 4.12%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:METHYLENE CHLORIDE (SARA III)

CAS:75-09-2

RTECS #:PA8

050000

Fraction by Wt: 24.10%

Other REC Limits:100 PM

OSHA PEL:500 PPM/C,1000; Z2

ACGIH TLV:50 PPM, A2; 9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 18.11%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:NAPHTA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:DE3030000

Fraction by Wt: 7.12%

Other REC Limits:STEL 400 PPM

OSHA PEL:100 PPM

Ingred Name:ETHYL A

LCOHOL (ETHANOL)

CAS:64-17-5

RTECS #:KQ6300000

Fraction by Wt: 1.72%

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: .91%

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:2-BUTOXYETHANOL

CAS:111-76-2

RTECS #:KJ8575000

Fraction by Wt: 1.10%

Other REC Limits:25 PPM

OSHA PEL:S, 50 PPM

ACGIH TLV:S, 25 PPM; 9293

Ingred Name:PROPANE

CAS:74-98-6

R

TECS #:TX2275000  
Fraction by Wt: 18.0%  
Other REC Limits:100 PPM  
OSHA PEL:1000 PPM  
ACGIH TLV:ASPHYXIAN; 9192

Ingred Name:ISOBUTANE  
CAS:75-28-5  
RTECS #:TZ4300000  
Fraction by Wt: 12.0%

Ingred Name:MINERAL SPIRITS  
CAS:64742-47-8  
Fraction by Wt: .60%

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:IRRITATION TO THE EYES, SKIN, MUCOUS

MEMBRANES, NOSE, THROAT/RESPIRATORY, HEADACHE, DROWSINESS,  
NARCOSIS,NAUSEA, DIZZINESS, UNCONSCIOUSNESS/ASPHYXIATION.  
PROLONGED/REPEATED LIQUID CONTACT MAY CAUSE DE FATTING OF THE SKIN,  
LEADING TO IRRITATION/DERMATITIS. INGESTION: ACCIDENTAL INGESTION  
IS UNLIKELY FROM AN AEROSOL CAN

Explanation of Carcinogenicity:NONE

Effects of Overexposure:PROLONGED/REPEATED LIQUID CONTACT MAY CAUSE  
DEFATTING OF THE SKIN, LEADING TO IRRITATION/DERMATITIS.  
LIVER/KIDNEY/LUNGS. INHALATIO

N OF HIGH LELS OF TOLUENE PRODUCED

CARDIAC SENSITIZATION MAY CAUSE FAT AL CHANGES IN HEART RYHTHMS,  
SHOWN TO BE ENHANCED BY HYPOXIA/INJECTION OF ADRENALINE-LIKE  
AGENTS.

Medical Cond Aggravated by Exposure:INHALATION TEST IN RATS: DUST FROM  
DRIED PRODUCTS PRODUCED AN INERT OR NUISANCE DUST RESPONSE IN THE  
LUNGS.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE PATIENT TO FRESH AIR. IF BREATHING STOPS,  
BEGIN ARTIFICIAL RESP

IRATION. SEEK MED ATT. EYES: FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINS. GET MED ATT. SKIN: WASH WITH SOAP & WATE R. INGESTION: CALL PHYSICIAN IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:TOC

Flash Point:-10F

Extinguishing Media:USE CO2, DRY CHEMICAL OR FOAM

Fire Fighting Procedures:USE FOG NOZZLES TO COOL CONTAINERS AND PREVENT BURSTING. WATER MAY BE INEFFECTIVE. FOG NOZZLES ARE PREFERABLE. WEAR GOGGLES & SCBA.

Unusu

al Fire/Explosion Hazard:EXPOSURE TO HEAT OR PROLONG EXPOSURE TO SUN MAY CAUSE BURSTING.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION, AVOID BREATHING VAPORS, VENTILATE AREA. WIPE UP WITH INERT MATERIALS AND PLACE IN APPROPRIATE CONTAINER.

Neutralizing Agent:DON'T INCINERATE/PUNCTURE AEROSOL. DON'T PLACE AEROSOL CANS IN HOME COMPACTOR.

===== Handling and Storage =====

===

Handling and Storage Precautions:DON'T STORE >120F. EXPOSURE TO HEAT OR PROLONGED EXPOSURE TO SUN MAY CAUSE BURSTING.

Other Precautions:INTENTIONAL MISUSE BY DILBERATELY CONCENTRATING VAPORS & INHALING CONTENTS CAN BE HARMFUL OR FATAL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:AVOID CONTINUOUS BREATHING OF VAPORS & SPRAY MIST. SCBA REQUIRED FOR CONCENTRATIONS >TLV.

Ventilation:USE WITH ADEQUATE VENTILATION. PROVIDE LOCAL EXHAUST

VENTILATION TO KEEP AIR

Evaporation Rate & Reference:FASTER THAN ETHER

Percent Volatiles by Volume:85%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:DON'T STORE >120F. KEEP FROM SPARKS, PILOT LIGHTS OR OPEN FLAME.

Hazardous Decomposition Products:CO2, CO, HYDROGEN CHLORIDE VAPOR & TRACES OF PHOSGENE.

===== Disposal Considerations =====

Waste Disposal Me

thods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND  
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume res  
ponsibility for the suitability of this information to their  
particular situation.