

THE EPOXYLITE CORPORATION -- EPOXY INSULATOR #6001 -- 5970-00-837-2150

=====
Product Identification
=====

Product ID:EPOXY INSULATOR #6001
MSDS Date:01/01/1985
FSC:5970
NIIN:00-837-2150
MSDS Number: BFRWN
=== Responsible Party ===
Company Name:THE EPOXYLITE CORPORATION
Address:9400 TOLEDO WAY
Box:19671
City:IRVINE
State:CA
ZIP:92713
Country:US
Emergency Phone Num:714-951-3026
CAGE:HO289
=== Contr
actor Identification ===
Company Name:THE EPOXYLITE CORPORATION
Address:9400 TOLEDO WAY
Box:19671
City:IRVINE
State:CA
ZIP:92713-9671
Country:US
Phone:714-951-3231
CAGE:11147
Company Name:THE EPOXYLITE CORPORATION
Address:9400 TOLEDO WAY
Box:19671
City:IRVINE
State:CA
ZIP:92713-9671
Country:US
Phone:714-951-3231
CAGE:HO289

=====
Composition/Information on Ingredients
=====

Ingred Name:SOLVENTS
Fraction by Wt: 61.0%

Ingred Name:RESIN
Fraction by Wt: 38.5%

Ingred Name:CATALYS

T

Fraction by Wt: 0.5%

=====
Hazards Identification
=====

Effects of Overexposure:HEADACHE, DIZZINESS, NAUSEA

=====
First Aid Measures
=====

First Aid:REMOVE TO FRESH AIR. IN CASE OF SKIN CONTACT-WASH WITH SOAP & WATER. EYES: FLUSH WITH WATER 15 MIN, SEEK MEDICAL ATTENTION. REMOVE CONTAMINATED CLOTHING & WASH BEFORE RE-USE.

=====
Fire Fighting Measures
=====

Flash Point:85F (TC
C)

Extinguishing Media:CARBON DIOXIDE, FOG, DRY CHEMICAL, FOAM

Fire Fighting Procedures:NONE

Unusual Fire/Explosion Hazard:SAME HAZARDS ORDINARILY ASSOCIATED WITH HYDROCARBONS.

=====
Accidental Release Measures
=====

Spill Release Procedures:BROADCAST ABSORBENT, REMOVE. FLUSH AREA WITH WATER, MOP UP WITH DETERGENT/WATER

=====
Handling and Storage
=====

Handling and Storage Precautions:AVOID CONTACT WIYH SKIN, EYES &
C

LOTHING. USE WITH ADEQUATE VENTILATION; AVOID EXCESSIVE TEMPERATURES. STORE IN CLOSED CONTAINERS.

=====
Exposure Controls/Personal Protection
=====

Ventilation:LOCAL EXHAUST PREFERABLE

Protective Gloves:RUBBER/PLASTIC

Eye Protection:FACE SHIELD

Other Protective Equipment:EYE BATH, SAFETY SHOWER, RUBBER APRON

Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:F3

Boiling Pt:=115.6C, 240.F

Vapor Pres:90

Spec Gravity:0.99

8

Evaporation Rate & Reference:0.5 (BU AC = 1)

Solubility in Water:INSOLUBLE

Appearance and Odor:AMBER LIQUID; AROMATIC HYDROCARBON

Percent Volatiles by Volume:65

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

CARBON MONOXIDE; CARBON DIOXIDE; OXIDES OF NITROGEN

Stability Condition to Avoid:EXPOSURE TO HEAT & OPEN FLAME

Hazardous Decomposition Products:CARBON MONOXIDE; CARBON DIOXIDE;
OXIDES OF NITROGEN

=====

= Disposal Considerations =====

Waste Disposal Methods:DUMP IN LANDFILL OR INCINERATE, WHICHEVER
PROCEDURE IS IN ACCORDANCE WITH LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person u

tilizing this

document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.