

EASTMAN KODAK CO. -- 140 8988,HC-110 DEVELOPER (PRE 9/85) -- 6750-00-837-7257
===== Product Identification =====

Product ID:140 8988,HC-110 DEVELOPER (PRE 9/85)

MSDS Date:06/18/1980

FSC:6750

NIIN:00-837-7257

MSDS Number: BFRWX

=== Responsible Party ===

Company Name:EASTMAN KODAK CO.

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-722-5151

Emergency Phone N

um:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

===== Composition/Information on Ingredients =====

Ingred Name:HYDROQUINONE (SARA III)

CAS:123-31-9

RTECS #:MX3500000

Fraction by Wt: 5-10%

OSHA PEL:2 MG/M3

ACGIH TLV:2 MG/M3; 9192

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:ETHANOLAMIN

E

CAS:141-43-5

RTECS #:KJ5775000

Fraction by Wt: 5-10%

OSHA PEL:3 PPM/6 STEL

ACGIH TLV:3 PPM/6 STEL; 9192

Ingred Name:DIETHANOLAMINE (SARA III)

CAS:111-42-2

RTECS #:KL2975000

Fraction by Wt: 50-55%

OSHA PEL:3 PPM

ACGIH TLV:3 PPM; 9192

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:AQUEOUS SOLUTION, NON-HAZARDOUS, UNIDENTIFIED COMPONENTS; WT%
BY DIFFERENCE

Fraction by Wt: 32.5%

Ingred Name:DIETHANOLAMINE-SULFUR DIOXIDE COMPLEX

CAS:63149-47-3

Fraction by Wt: 1-5%

Other REC Limits:NONE SPECIFI

ED

=====
===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: CAUSES SKIN AND EYES

IRRITATION. PROLONGED SKIN CONTACT MAY CAUSE ALLERGIC REACTION.

Effects of

Overexposure:INHALE:IRRITNT;EYES:IRRITNT(VAPORS),BURNS(LIQUID);SKIN
:IRRITNT,BURNS,ALLERGIC SKIN REACTION.

=====
===== First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR,GIVE CPR/O

*2 IF NEED;EYES:FLUSH W

LG AMTS H*20 FOR 15 MIN;SKIN:FLUSH W LG AMTS H*20;INGEST:RINSE
MOUTH; GET IMMEDIATE MEDICAL ATTENTION FOR EYES OR INGEST.

=====
===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:SUITABLE FOR SURROUNDING FIRE.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND
PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY PRODUCE
DECOMPOSITION PRODUCTS. EXPOSED CONTAINERS M

RY RUPTURE IN HEAT OF
FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS.STOP LEAK.H*2O
SPRAY HOT CONTAINERS.ABSORB WITH COMMERCIAL ABSORBENT,SHOVEL INTO
WASTE DISPOSAL CONTAINERS;LG SPIL:DIKE WITH COMMERCIAL
ABSORBENT,TRANSFER INTO WASTE DISPO SAL CONTAINERS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED
ARE

A;PROTECT FROM PHYSICAL DAMAGE & AVOID SKIN CONTACT.KEEP
CONTAINERS TIGHTLY CLOSED.

Other Precautions:REMOVE & WASH CONTAMINATED CLOTHING.MAINTAIN STRICT
HYGIENE.USE OF NON-ALKALINE(ACID) TYPE HAND CLEANER REDUCES RISK OF
ALLERGIC SKIN REACTION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR APPROVED ORGANIC VAPOR RESPIRATOR IF
VENTILATION IS INADEQUATE

Ventilation:ADEQUATE TO ELIMINATE MISTS:MECHANICAL(GEN/LOCAL EXHAUST)
Protect

ive Gloves:IMPERVIOUS

Eye Protection:SAFETY/CHEM GOGGLES.

Other Protective Equipment:FULL WORK CLOTHING;FACE SHIELD WHEN
USING/MIXING PRODUCT.

Supplemental Safety and Health

THIS DATA IS FOR MATL MANUFACTURED BEFORE SEPT 85. FOR MATL PRODUCED
AFTER THIS DATA,SEE PNI B.KEY1:N1.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:>212F,>100C

Vapor Pres:12

Vapor Density:2.09

Spec Gravity:1.21

pH:9.0

Solubility in Water:COMPLETE

Appearance and O

odor:BROWN AQUEOUS MIXTURE;AMMONIA TYPE ODOR.
Percent Volatiles by Volume:69

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
MINERAL ACIDS
Stability Condition to Avoid:EXCESSIVE HEAT
Hazardous Decomposition Products:SULFUR DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:KEEP IN COVERED CONTAINERS.PENDING
DISPOSAL.HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE
INTE
RNATIONAL,FEDERAL,STATE,& LOCAL REGULATIONS.MFG SUGGESTS FLUSH
TO SEWER WITH COPIOUS AMOUNTS OF WATER.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional adv
ice to verify and
assume responsibility for the suitability of this information to their
particular situation.