View NSN Online: https://aerobasegroup.com/nsn/8040-00-843-3461

CLIFTON ADHESIVE INC -- MMM-A-121 -- 8040-00-843-3461

Product ID:MMM-A-121 MSDS Date:01/01/1987

FSC:8040

NIIN:00-843-3461

MSDS Number: BFSGF === Responsible Party ===

Company Name: CLIFTON ADHESIVE INC

Address:39 AVENUE C

Box:8

City:BAYONNE

State:NJ

ZIP:07002-3417

Country:US CAGE:79833

=== Contractor Identification ===

Company Name: CLIFTON ADHESIVE INC

Address:BU RGESS PL

Box:City:WAYNE

State:NJ ZIP:07470 Country:US

Phone:201-694-0845; 973-694-0845

CAGE:79833

Company Name: STEVEN INDUSTRIES

Address:39 AVENUE C

Box:8

City:BAYONNE

State:NJ

ZIP:07002-3417

Country:US

Phone:201-437-6501

CAGE:33150

====== Composition/Information on Ingredients ========

Ingred Name: METALLIC OXIDES

Fraction by Wt: 1%

Ingred Name:VEHICLE Fraction by Wt: 11%

Ingred Name:SOLVENT Fraction by Wt: 82% ACGIH TLV:525PPM

Ingred Name: TOLUENE (SARA III)

CAS:108-88-3

RTEC

S #:XS5250000 Fraction by Wt: 17% Other REC Limits:NONE RECOMMENDED OSHA PEL:200 PPM; Z-2 ACGIH TLV:S, 50 PPM; 9394 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS
Ingred Name:HEXANE (N-HEXANE) CAS:110-54-3 RTECS #:MN9275000 Fraction by Wt: 50% OSHA PEL:500 PPM ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB
============ Hazards Identification ==============
Effects of Overexposure:NARCOSIS AND/OR POSSIBLE HEADACHE OR BRONCHIAL CATARRH
=========== First Aid Measures ====================================
First Aid:FRESH AIR-SEE DR.
======================================
Flash Point:15 F TCC -9C Lower Limits:1.2 Upper Limits:13 Extinguishing Media:DRY CHEMICAL,CO*2,FOAM, TRICHORETHANE Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS SHOULD BE WORN. Unusual Fire/Explosion Hazard:KEEP AWAY FROM OPEN FLAME,SPARKS,HOT SURFACES AND OXIDIZERS
========= Accidental Release Measures ============

Sp

ill Release Procedures:WIPE UP
======================================
Handling and Storage Precautions:DO NOT STORE NEAR HEAT OR IN DIRECT SUNLIGHT. STORE IN SOLVENT STORAGE AREA.
====== Exposure Controls/Personal Protection ========
Ventilation:LOCAL EXHAUST Protective Gloves:YES Eye Protection:SAFETY GLASSES Other Protective Equipment:HAND CREAM Supplemental Safety and Health ACETONE AL315000,23%,1000PPM;MEK OS0175000,10% 200PPM; PHENOLIC RESI N
========= Physical/Chemical Properties =============
HCC:F2 Boiling Pt:B.P. Text:132 F 55 C Vapor Pres:185 Vapor Density:0.75 Spec Gravity:0.8 Appearance and Odor:OFF WHITE,KETONE AND NAPTHANE ODOR Percent Volatiles by Volume:88
======================================
Stability Indicator/Materials to Avoid:YES
========= Disposal Considerations ==============
Waste Disposal Methods:SOLVENT DISPOSAL PROCEDURES
Disclaimer (pro

vided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.