

FULLER H B CO -- SC-849,SOLVENT CEMENT,POLYCHLOROPRENE -- 8040-00-843-3461

=====  
Product Identification  
=====

Product ID:SC-849,SOLVENT CEMENT,POLYCHLOROPRENE

MSDS Date:01/01/1987

FSC:8040

NIIN:00-843-3461

MSDS Number: BFSGH

=== Responsible Party ===

Company Name:FULLER H B CO

Address:2400 KASOTA AVE

City:SAINT PAUL

State:MN

ZIP:55108-1511

Country:US

Info Phone Num:612-645-3401 / FAX 612-645-6936

Emergency Phone Num:612-645-3401

CAGE:92528

=== Contractor Identification ===

Company Name:FULLER H B CO

Address:2400 KASOTA AVE

Box:City:ST PAUL

State:MN

ZIP:55108-1511

Country:US

Phone:612-645-3401

CAGE:92528

=====  
Composition/Information on Ingredients  
=====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 11%.

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE (SARA III)

CAS:67-64

-1

RTECS #:AL3150000

Fraction by Wt: 29%.

OSHA PEL:1000PPM

ACGIH TLV:750PPM/1000STEL;9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:NAPHTA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:DE3030000

Fraction by Wt: 40%.

OSHA PEL:100 PPM

=====  
===== Hazards Identification =====

Effects of Overexposure:HEADACHE,NAUSEA,DIZZINESS,IMPAIRMENT OF  
COORDINATION

=====  
===== First Aid Measures =====

First Aid:INHAL:REMOVE TO  
FRESH AIR, GIVE ARTIFICIAL RESP IF NECESSARY.  
CALL MD. SKIN:REMOVE MATERIAL WITH SOAP & WATER. EYE:IMMEDIATELY  
FLUSH W/WATER AT LEAST 15 MIN. CALL MD. INGEST:CALL MD. DO NOT  
INDUCE VOM ITING.

=====  
===== Fire Fighting Measures =====

Flash Point:0F TCC  
Lower Limits:1.2  
Extinguishing Media:CO\*2, FOAM, DRY CHEMICAL  
Fire Fighting Procedures:DO NOT USE WATER  
Unusual Fire/Explosion Hazard:VAPOR MAY IGNITE EXPLOSIVELY. VAPOR MAY  
CAUSE FLASH FIRE.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE OR EXTINGUISH ALL SOURCES OF FLAME,  
HEAT, SPARKS. TURN OFF ALL ELECTRIC MOTORS IN AREA & VENTILATE.  
WEAR RUBBER GLOVES & USE RAGS. DISPOSE OF RAGS IN SEALED  
CONTAINERS.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:DANGER! EXTREMELY FLAMMABLE. VAPOR MAY  
CAUSE FLASH FIRE.

Other Precautions:VAPORS HARMFUL.PRODUCT IS HARMFUL OR FATAL I

S

SWALLOWED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:MSHA/NIOSH APPROVED ORGANIC VAPOR MASK IF VENTILATION INADEQUATE

Ventilation:GENERAL DILUTION TO KEEP VAPOR CONC. BELOW TLV.

Protective Gloves:SOLVENT RESIST.

Eye Protection:SAFETY GLASSES W/SIDE SHLD

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:130 TO 235F

Vapor Pres:180

Vapor Density:1

Spec Gravity:0.8

2

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:86

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:FLAME, SPARK & HEAT

Hazardous Decomposition Products:CO,CO\*2, HCL, HYDROCARBONS

===== Disposal Considerations =====

Waste Disposal Methods:LANDFILL UNLESS PROHIBITED BY LAW. OTHERWISE INCINERATE. DO NOT INCINERATE IN SEALED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation

ion.