

AMERON INDUSTRIAL COATINGS DIV.,PRATT AND LAMBERT -- 744-102 -- 8010-00-844-1305

=====
Product Identification
=====

Product ID:744-102

MSDS Date:01/01/1985

FSC:8010

NIIN:00-844-1305

MSDS Number: BFSHN

=== Responsible Party ===

Company Name:AMERON INDUSTRIAL COATINGS DIV.,PRATT AND LAMBERT

Emergency Phone Num:316-733-1361

CAGE:09869

=== Contractor Identification ===

Company Name:AMERON INDUSTRIAL

COATINGS DIVISION

Address:201 N BERRY ST

Box:City:BREA

State:CA

ZIP:92621-3904

Country:US

Phone:714-529-4597

CAGE:09869

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHYL BENZENE (SARA III)

CAS:100-41-4

RTECS #:DA0700000

OSHA PEL:100 PPM/125 STEL

ACGIH TLV:100 PPM/125STEL 9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

OSHA PEL:100 PPM

Ingred Name:LEAD CHROMATE (OSHA PEL FOR

LEAD FROM 29CFR
1910.1025),(CRO3 CEILING 0.1 MG/M3)
CAS:7758-97-6
RTECS #:GB2975000
OSHA PEL:0.05 MG/M3 (PB)
ACGIH TLV:0.05MG/M3(CR)A2;8990

Ingred Name:ISOBUTYL ALCOHOL (SARA III)
CAS:78-83-1
RTECS #:NP9625000
OSHA PEL:100 PPM
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)
CAS:111-15-9
RTECS #:KK8225000
OSHA PEL:S,100 PPM
ACGIH TLV:S, 5 PPM; 9192

=====
Hazards Identification
=====

Effects of Overexposure:EYE,THROAT,SKIN,LUNG
IRRITANT;COMA;UNCONSCIOUSNESS;CONFUSION;NERVOUS SYSTEM DEPRESSANT

=====
First Aid Measures
=====

First Aid:WASH SKIN WELL.FLUSH EYES WITH WATER. REMOVE TO FRESH AIR.
REMOVE CONTAMINATED CLOTHING. GIVE ARTIF.RESP. IF NEEDED CALL MD.

=====
Fire Fighting Measures
=====

Flash Point:50F, 9C TCC
Lower Limits:0.9
Extinguishing Media:FOAM,DRY CHEM.,CARBON DIOXIDE(POLYM
ERFOAM)
Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS
Unusual Fire/Explosion Hazard:AVOID FIRE,HEAT,SPARKS,IGNITION
SOURCES,STORAGE IN DIRECT SUNLIGHT;HEAT MAY BURST CANS.

=====
Accidental Release Measures
=====

Spill Release Procedures:VENTILATE AREA,KEEP FROM FLAME,FIRE,SPARKS,
IGNITION SOURCES;DO NOT BREATHE VAPORS;CLEAN UP WITH ABSORBENT
MATERIAL;USE NON-SPARKING TOOLS.

=====
Handling and Storage
=====

=

Handling and Storage Precautions:KEEP CONTAINERS CLOSED,UPRIGHT,AWAY FROM FIRE,FLAME,SPARKS,IGNITION SOURCES,DIRECT SUNLIGHT;DO NOT STORE ABOVE 120F.NFPA CLASS I FLAMMABLE BLDG.

Other Precautions:DO NOT TAKE INTERNALLY;GROUND ALL CONTAINERS WHEN POURING;DO NOT FLAME CUT,BRAZE,OR WELD COATED MATERIAL WITHOUT RESPIRATOR OR GOOD VENTILATION.

===== Exposure Controls/Personal Protection =====

Ventilation:LOCAL EXHAUST
Protective Gloves:PROTECTIVE
Eye Protection:
GOGGLES/SAFETY GLASSES
Supplemental Safety and Health
BOILING RANGE IS 223-329F.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:223F106C
Appearance and Odor:LIQUID;COLOR-RED
Percent Volatiles by Volume:64.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:FIRES,HEAT,HOT SURFACES

===== Disposal Considerations =====

Waste Disposal Methods:LOCAL,STATE AND FED. LAWS. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume res

possibility for the suitability of this information to their particular situation.