

SEYMOUR OF SYCAMORE, INC -- OLIVE DRAB, GP-0001-4064 -- 8010-00-846-5117
===== Product Identification =====

Product ID:OLIVE DRAB, GP-0001-4064
MSDS Date:01/18/1988
FSC:8010
NIIN:00-846-5117
MSDS Number: BFSKR
=== Responsible Party ===
Company Name:SEYMOUR OF SYCAMORE, INC
Address:917 CROSBY AVE
City:SYCAMORE
State:IL
ZIP:60178
Info Phone Num:(815) 895-9101
Emergency Phone Num:(815) 895-9101
CAGE
:59581
=== Contractor Identification ===
Company Name:SEYMOUR OF SYCAMORE
Address:917 CROSBY AVE.
Box:City:SYCAMORE
State:IL
ZIP:60178-1343
Country:US
Phone:815-895-9101/800-255-3924
CAGE:59581

===== Composition/Information on Ingredients =====

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: .55%
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:METHYLENE CHLORIDE (SARA III)
CAS:75-09-2
RTECS #:PA8050000
Fraction by Wt: 24.66%
O

ther REC Limits:100 PM
OSHA PEL:500 PPM/C,1000; Z2
ACGIH TLV:50 PPM, A2; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 18.52%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:MEDIUM ALIPHATIC NAPHTHA
CAS:64742-88-7
Fraction by Wt: 1.04%

Ingred Name:VM&P NAPHTHA (LIGROINE)
CAS:8032-32-4
RTECS #:OI6180000
Fraction by Wt: 7.08%
Other REC Limits:STEL 400 PPM
OSHA P
EL:300 PPM/400 STEL
ACGIH TLV:300 PPM; 9192

Ingred Name:ETHYL ALCOHOL (ETHANOL)
CAS:64-17-5
RTECS #:KQ6300000
Fraction by Wt: 1.76%
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM; 9192

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: .56%
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:2-BUTOXYETHANOL
CAS:111-76-2
RTECS #:KJ8575000
Fraction by Wt: 1.12%
Other REC Limits:25 PPM
OSHA PEL:S, 50

PPM
ACGIH TLV:S, 25 PPM; 9293

Ingred Name:PROPANE
CAS:74-98-6
RTECS #:TX2275000
Fraction by Wt: 18.0%
Other REC Limits:100 PPM
OSHA PEL:1000 PPM
ACGIH TLV:ASPHYXIAN; 9192

Ingred Name:ISOBUTANE
CAS:75-28-5
RTECS #:TZ4300000
Fraction by Wt: 12.0%

Ingred Name:LEAD CARBONATE (OSHA PEL FROM 29CFR 1910.1025)
CAS:598-63-0
RTECS #:OF9275000
Fraction by Wt: .11%
OSHA PEL:0.05 MG/M3 (PB)
ACGIH TLV:0.15 MG/M3 (PB);8990

=====
===== Hazards Identification =====

Routes of Ent

ry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:YES

Health Hazards Acute and Chronic:INHALATION OF HIGH LELS OF TOLUENE
PRODUCED CARDIAC SENSITIZATION. SENSITIZATION MAY CAUSE FATAL
CHANGES IN HEART RHYTHMS. IRRITATION OF MUCOUS MEMBRANES, EYES,
NOSE & THROAT, HEADACHE, DIZZINESS, NAU SEA, UNCONSCIOUSNESS,
ASPHYXIATION, DROWSINESS, FATIGUE/NARCOSIS. INGESTION: ACCIDENTAL
IS UNLIKELY FROM AN AEROSOL CAN.

Explanation of Carcinogen

icity:CONTAINS LEAD: LEAD CHROMATE & LEAD
MOLYBDATE ARE IARC/OSHA CARCINOGENS.

Effects of Overexposure:PROLONGED/REPEATED LIQUID CONTACT MAY CAUSE
DEFATTING OF THE SKIN, LEADING TO IRRITATION & DERMATITIS.
MISTS/FUMES SHOULD BE MINIMIZED. LIVER, KIDNEYS, LUNGS, LOSS OF
APPETITE, ANEMIA, DISTURBANCE OF SLEEP & FATIGUE. CARDIAC EFFECT
WAS SHOWN TO BE ENHANCED BY HYPOXIA OR THE INJECTION OF
ADRENALINE-LIKE AGENTS.

=====
===== First Aid Measures =====

=====

First Aid:INHALATION: REMOVE PATIENT TO FRESH AIR. IF BREATHING STOPS, BEGIN ARTIFICIAL RESPIRATION. EYES: FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINS. SKIN: WASH WITH SOAP & WATER. INGESTION: CALL PHYSICIA N IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:-10F

Extinguishing Media:USE CO2, DRY CHEMICAL OR FOAM

Fire Fighting Procedures:USE FOG NOZZLES TO COOL CONTAINERS AND PREVENT BURSTING. WATE

R MAY BE INEFFECTIVE. FOZ NOZZLES ARE PREFERABLE.

WEAR GOGGLES & SCBA.

Unusual Fire/Explosion Hazard:EXPOSURE TO HEAT MAY CAUSE BURSTING OF AEROSOL CAN.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION, AVOID BREATHING VAPORS, VENTILATE AREA. WIPE UP WITH INERT MATERIALS AND PLACE IN APPROPRIATE CONTAINER.

Neutralizing Agent:DON'T INCINERATE/PUNCTURE AEROSOL. DON'T PLACE AEROSOL CANS IN HOME COMPACTO

R.

===== Handling and Storage =====

Handling and Storage Precautions:DON'T STORE >120F. EXPOSURE TO HEAT OR PROLONG EXPOSURE TO SUN MAY CAUSE BURSTING.

Other Precautions:INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING VAPORS & INHALING CONTENTS CAN BE HARMFUL OR FATAL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:AVOID CONTINUOUS BREATHING OF VAPORS & MIST. SCBA REQUIRED FOR CONCENTRATIONS ABOVE TLV.

Ventilation:USE WITH ADEQUATE VENTILATION. PROVIDE LOCAL EXHAUST VENTILATION TO KEEP AIR

Percent Volatiles by Volume:85%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID STRONG OXIDIZING AGENTS

Stability Condition to Avoid:DON'T STORE >120F. KEEP AWAY FROM SPARKS, PILOT LIGHTS OR OPEN FLAME.

Hazardous Decomposition Products:FUMES MAY CONTAIN CO2, CO. HYDROGEN CHLORIDE VAPOR & TRACES OF PHOSGENE.

=====

== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document

should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.