View NSN Online: https://aerobasegroup.com/nsn/8040-00-851-0211

DOW CORNING CORP. -- SILASTIC 732 RTV SEALANT -- 8040-00-851-0211

Product ID:SILASTIC 732 RTV SEALANT MSDS Date:01/01/1985 FSC:8040 NIIN:00-851-0211 **MSDS Number: BFSQT** === Responsible Party === Company Name: DOW CORNING CORP. Emergency Phone Num: (517) 496-5900 CAGE:5D028 === Contractor Identification === Company Name: DOW CORNING CORP Address:3901 S SAGINAW RD Box :997 City:MIDLAND State:MI ZIP:48686-0997 Country:US Phone:517-496-6000/517-496-6315 CAGE:5D028 Company Name: DOW CORNING CORP Address:2200 W SALZBURG RD Box:City:AUBURN State:MI ZIP:48611 Country:US Phone:517-496-4388 CAGE:71984

Ingred Name:ACETOXYSILANE Fraction by Wt: 5.0%

Effects of Overexposure:IRRITATES EYES. PROLONGED OR REPEATED CONTACT MAY IRRI

======================================
First Aid:WIPE OFF. FLUSH W/ WATER. OBTAIN MEDICAL ATTN FOR EYES IF NECESSARY
======================================
Flash Point:>250F OC Extinguishing Media:CO*2 OR FOAM Fire Fighting Procedures:SELF-CONTAINED BRTHNG APPAR & PROTECTIVE CLOTHING
Unusual Fire/Explosion Hazard:NOT KNOWN TO DOW CORNING
======================================
Spill Rele ase Procedures:USE ABSORBENT MATERIAL TO COLLECT & CONTAIN FOR SALVAGE OR DISPOSAL
======================================
Handling and Storage Precautions:STORE BELOW 90F. USE REASONABLE CARE.
======================================
Respiratory Protection:NIOSH/MSHA APPRVD ACID VAPOR TYPE Ventilation:MFR RECM MECHANICAL VENTILATION Protective Gloves:RUBBER/PLASTIC Eye Protection:SAFETY GLASSES Supplemental Safety and Health MFR SUG
GESTS TLV OF 10 PPM (BASED ON LIBERATED ACETIC ACID). % VOLATILE BY VOLUME: 300F Vapor Pres: