

GENERAL ELECTRIC CO. SILICONE PRODUCTS BUSINESS DE -- SF96-350 -- 9150-00-851-4257  
===== Product Identification =====

Product ID:SF96-350  
MSDS Date:03/23/1990  
FSC:9150  
NIIN:00-851-4257  
MSDS Number: BFSQY

=== Responsible Party ===

Company Name:GENERAL ELECTRIC CO. SILICONE PRODUCTS BUSINESS DE  
Address:HUDSON RIVER ROAD  
City:WATERFORD  
State:NY  
ZIP:12188  
Country:US

Info Phone Num:518-237-3330

Emerge

ncy Phone Num:518-237-3330

Preparer's Name:GCD

CAGE:01139

=== Contractor Identification ===

Company Name:DAVIS HOWLAND OIL CORP.

Address:200 ANDERSON AVE.

City:ROCHESTER

State:NY

ZIP:14607

Country:US

Phone:716-473-6650

CAGE:5A565

Company Name:GENERAL ELECTRIC CO, SILICONE PRODUCTS BUSINESS DEPT

Address:260 HUDSON RIVER RD

Box:City:WATERFORD

State:NY

ZIP:12188

Country:US

Phone:518-237-3330/800-332-3390

CAGE:01139

===== Composition/Information on Ingredients =====

Ingred Name:N

ON-HAZARDOUS INGREDIENTS (INERT)

Other REC Limits:NONE SPECIFIED

Ingred Name:DIMETHYL SILOXANE (DOW CORNING 200)

CAS:63148-62-9

RTECS #:JT6484500

Fraction by Wt: 80-99%

Other REC Limits:NONE SPECIFIED

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:LD50 ORAL RAT IS > 40000 MG/KG

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: NONE SPECIFIED BY MANUFACTURER.

CHRONIC: NONE KNOWN.

Explanation of Carcinogenicity:NONE SPECIFIED BY MANUFACTURER.

Effects of Overexposure:MAY CAUSE MILD EYE IRRITATION. EFFECTS ON SKIN  
NONE SPECIFIED BY MANUFACTURER.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====  
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. GET  
MEDICAL ATTENTION IF IRRITATION PERSISTS. SKIN: WASH WITH SOAP AND  
WATER. INHALATION:

EXPOSURE BY INHALATION NOT LIKELY. INGESTION:

RINSE MOUTH WITH WATER SEVERAL TIMES. NOTE TO PHYSICIAN: NONE  
KNOWN.

=====  
===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:575F,302C

Extinguishing Media:ALL STANDARD FIREFIGHTING MEDIA.

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN CASE OF FIRES.

Unusual Fire/Explosion Hazard:NONE KNOWN

=====  
===== Accidental Release Measures =====

Spill Release Procedu

res:USE APPROPRIATE PROTECTIVE EQUIPMENT;WIPE,  
SCRAPE OR SOAK UP IN AN INERT MATERIAL AND PUT IN A CONTAINER FOR  
DISPOSAL. WASH WALKING SURFACES WITH DETERGENT AND WATER TO REDUCE  
SLIPPING HAZARD.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:NO SPECIAL REQUIREMENTS; USE NORMAL  
PROCEDURES. KEEP CONTAINER CLOSED WHEN NOT IN USE.

Other Precautions:AVOID CONTACT WITH SKIN AND EYES. WASH AFTER EACH  
USE.

=====  
===== Expo  
sure Controls/Personal Protection =====

Respiratory Protection:NO SPECIAL REQUIREMENTS UNDER ORDINARY  
CONDITIONS. USE ADEQUATE VENTILATION.

Ventilation:NO SPECIAL REQUIREMENTS.

Protective Gloves:RUBBER.

Eye Protection:CHEMICAL SPLASH GOGGLES.

Other Protective Equipment:EYE WASH STATIONS.

Work Hygienic Practices:WASH AFTER HANDLING. NO EATING OR STORING FOOD  
PRODUCTS WHERE CHEMICALS ARE USED.

Supplemental Safety and Health

ACUTE DERMAL LD50 NON-IRRITATING RABBIT.

=====  
===== Physical/Chemical Properties =====

HCC:V6

Vapor Pres:NONE

Spec Gravity:0.97

Evaporation Rate & Reference:>1.0 (BUTYL ACETATE = 1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR, ODORLESS LIQUID

Percent Volatiles by Volume: