View NSN Online: https://aerobasegroup.com/nsn/8040-00-853-8913

Product ID:N-HEXANE ASTM D 1836-64 MSDS Date:01/01/1987 FSC:8040 NIIN:00-853-8913 MSDS Number: BFSVG === Responsible Party === Company Name: VAN WATERS AND ROGERS Address:2256 JUNCTION AVE **City:SAN JOSE** State:CA ZIP:95131 Country:US Info Phone Num:408-435-8700 Emergency Phone Num:408-435-8700/80 0-424-9300(CHEMTREC) CAGE:0AN91 === Contractor Identification === Company Name: VAN WATERS AND ROGERS Address:2256 JUNCTION AVE City:SAN JOSE State:CA ZIP:95131 Country:US Phone:408-435-8700/800-424-9300(CHEMTREC) CAGE:0AN91

Ingred Name:HEXANE (N-HEXANE) CAS:110-54-3 RTECS #:MN9275000 Fraction by Wt: >95% OSHA PEL:500 PPM ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

================== Hazards Identification =

Effects of Overexposure: VAPORS ARE INTOXICATING & NARCOTIC, IRRITATING TO MUCOUS MEMBRANE.IT IS HARMFUL/FATAL IF SWALLOWED.

First Aid:INHALE:REMOVE TO FRESH AIR,KEEP VICTIM WARM & QUIET,CALL PHYSICIAN IMMEDIATELY,IF BREATHING HAS STOPPED,GIVE ARTIFICAL RESPIRATION;IF.SWALLOWED,DO NOT INDUCE VOMITING;AVOID FREQUENT & PROLONGED CONTAC T WITH SKIN.

======== Fire Fighting Measur

Flash Point:-25F/-31.7C(TCC) Lower Limits:1.1 Upper Limits:7.5 Extinguishing Media:CO*2, FOAM, DRY CHEM. Fire Fighting Procedures:NONE Unusual Fire/Explosion Hazard:FORMS COMBUSTIBLE AND/OR EXPLOSIVE MIXTURES WITH AIR.

Spill Release Procedures:MATL IS VERY VOLATILE & HIGHLY FLAMMABLE.SPILLED MATL MAY BE PUMPED INTO ANOTHER CONTAINER OR ABSORBED AND REMOVED FROM THE AREA.ALL FLAMES,SPRARKS & IGNITION

SOURCES SHOULD BE KEPT OUT OF AREA;NON-SP ARKING TOOLS USED.

Handling and Storage Precautions:STORE IN COOL,DRY WELL VENTED,LOW FIRE RISK AREA. PROTECT FR HEAT,SHOCK KEEP CONTAINERS CLOSED.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection: IF EXPOSD TLV, NIOSH/MESA APPR SELF-CNTND BRTHG APP (POS PR MODE) Ventilation: MECH(GEN/LOCAL EXHAUST) TO MAINT