

3M COMPANY -- EC-801 INDUSTRIAL SEALANT (B-2) -- 8030-00-855-5015

=====
Product Identification
=====

Product ID:EC-801 INDUSTRIAL SEALANT (B-2)

MSDS Date:01/01/1987

FSC:8030

NIIN:00-855-5015

Kit Part:Y

MSDS Number: BFSWY

=== Responsible Party ===

Company Name:3M COMPANY

Emergency Phone Num:(612) 733-1110

CAGE:76381

=== Contractor Identification ===

Company Name:3M MINNESOTA MINING AND MFG CO ADHE

SIVES SEALERS DIV

Address:3M CTR

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:800-364-3577/651-737-6501(24 HOURS)

CAGE:04963

Company Name:MINNESOTA MINING AND MFG CO, DBA 3M

Address:3M CENTER BLDG 224-5S-04

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:866-556 5712 / 612-733-1110

CAGE:76381

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM BASE SOLVENT

Fraction by Wt: 3.0%

ACGIH TLV:UNK

Ingred Name:POLYSULFIDE RUBBER (MF

R'S MSDS SHOWS THIS INGRED + NIOSH

3,4,& 5 + SILICA PIGM.+ H*2O= 97

Fraction by Wt: UNK

ACGIH TLV:UNK

Ingred Name:PHENOLIC RESIN

Fraction by Wt: UNK

ACGIH TLV:UNK

Ingred Name:CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000

Fraction by Wt: UNK

OSHA PEL:3.5 MG/M3

ACGIH TLV:3.5 MG/M3; 9192

Ingred Name:MAGNESIUM ACETATE(MFR'S MSDS SHOWS THIS INGRED.+ NIOSH

2,3,& 4 + SILICA PIGM.+ H*2O = 97)

CAS:142-72-3

RTECS #:AI5600000

Fraction by Wt: UNK

ACGIH TLV:UNK

==== Hazards Ident
ification =====

Effects of Overexposure:MAY BE IRRITATING TO EYES.

==== First Aid Measures =====

First Aid:EYE:FLUSH EYES W/ PLENTY OF WATER. CALL A PHYSICIAN. SKIN:
WASH W/ SOAP & WATER.

==== Fire Fighting Measures =====

Extinguishing Media:CO*2, FOAM, DRY CHEMICALS

Fire Fighting Procedures:NONE

Unusual Fire/Explosion Hazard:NONE

==== Accidental Release Measures =====

=

Spill Release Procedures:COLLECT SPILLED MATERIAL. WIPE UP AREA.

===== Handling and Storage =====

Other Precautions:NOTE: THE ACCELERATOR USED W/ THIS PRODUCT CONTAINS LEAD. SEE SEPARATE MATERIAL SAFETY DATA SHEET ON ACCELERATOR.

===== Exposure Controls/Personal Protection =====

Ventilation:MFR RECM MECHANICAL EXHAUST

Eye Protection:SAFETY GLASSES

Supplemental Safety and Health

OTHER P/N: SCOTCHSEAL 801(B2) IND SLNT. PT A OF TWO PAR

T EC-801 (B2)

IND SLNT KIT. 3M GENERIC ID:62-0801-XXXX-X.ADDED IN GR: SILICA PIGMENT & WATER. QTY: N/K KEY1:N1.

===== Physical/Chemical Properties =====

HCC:D1

Spec Gravity:1.4

Appearance and Odor:BLACK - SULFUR ODOR

Percent Volatiles by Volume:0.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:CO, CO*2 & S DECOMPOSITION PRODUCTS NO

===== Disposal Considerations =====

Waste Disposal Methods:MFR RECM - INCINERATE PROPERLY. DO NOT LANDFILL. DISPOSE IAW FED., STATE & LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.