

PRATT & LAMBERT-WICHITA DIV. -- 742-102;TT-E-489F COMPL,CLA 11105 RED -- 8010-00-889-7345

=====
Product Identification
=====

Product ID:742-102;TT-E-489F COMPL,CLA 11105 RED

MSDS Date:01/01/1987

FSC:8010

NIIN:00-889-7345

MSDS Number: BFTXZ

=== Responsible Party ===

Company Name:PRATT & LAMBERT-WICHITA DIV.

Emergency Phone Num:(316) 733-1361

CAGE:KO010

=== Contractor Identification ===

Company Nam

e:PRATT & LAMBERT-WICHITA DIV.

Box:2153

CAGE:KO010

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: >50%.

OSHA PEL:100 PPM

Ingred Name:TOLUIDINE RED

CAS:2425-85-6

RTECS #:QK4247000

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

=====
Hazards Identification
=====

Effects o

f Overexposure:INH:ANESTHETIC,IRRIT OF RESP TRACT OR ACUTE CNS
DEPRSSN W/HDACHE,DIZ,UNCON,COMA.SKIN & EYE:IRRIT

=====
First Aid Measures
=====

First Aid:IN CASE OF CONTACT,FLUSH SKIN & EYES W/PLENTY OF WATER WHILE
REMOVING CONTAMINATED CLOTHING.IF INHALED,REMOVE TO FRESH AIR.CALL
A PHYSICIAN IF SYMPTOMS PERSIST

=====
Fire Fighting Measures
=====

Flash Point:104F TCC

Lower Limits:1.1

Extinguishing Media:SM FIR

ES:CO*2,DRY CHEM. LG FIRES:POLYMER FOAM
PREFERRED

Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY
EXPLODE DUE TO PRESSURE BUILD UP.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION(FLAME,HOT
SURFACES, & ELECTRICAL,STATIC, OR FRICTIONAL SPARKS).AVOID
BREATHING VAPORS.VENTILATE AREA.REMOVE W/INERT ABSORBENT &
NON-SPARKI
NG TOOLS.

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LG QTY
IN BUILDINGS DESIGNED TO COMPLY W/OSHA 1910.106.DO NOT TAKE
INTERNALLY.ADD LABEL WARNING

Other Precautions:GROUND CONTAINERS WHEN POURING.AVOID FREE FALL OF LIQ
IN EXCESS OF FEW IN. DO NOT FLAME CUT,BRAZE OR WELD COATED MATERIAL
W/O APPROVED RESPIRATOR OR APPROPRIATE VENTILATION.
DOT:COMBUSTIBLE.

=====
Exposure Control
s/Personal Protection
=====

Respiratory Protection:NIOSH/MSHA APPRVD. RESTRICT VENT.CHEM-MECH
FLTR.CLSD:AIR-LINE TYPE

Ventilation:GEN DILTN/LOCAL EXHST TO KEEP TLV/LEL BELOW LIMIT,REMV FUME
Protective Gloves:YES

Eye Protection:YES,FOR SPLASH

Other Protective Equipment:AVOID LONG EXPOSURE TO CONTAM CLOTHING

Supplemental Safety and Health

ADDRESS:630 EAST 13TH,ANDOVER,KS 67002.THIS PRODUCT IS AN ENAMEL ALKYD
GLOSS.VAPOR PRESSURE BASED ON MINERAL SPIRITS IS 3.2.VAPOR DENSITY

:

HEAVIER THAN AIR.WT PER GAL:7.8 LBS.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:311-373F

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:62.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:AVOID FIRES,HEAT & HOT SURFACES

===== Disposal Considerations =====

Waste Disposal Methods:DO NO

T INCINERATE CLOSED CONTAINER.DISPOSE IN

ACCORDANCE W/ FED.,STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.