

CORONADO PAINT CO -- WHITE TRAFFIC PAINT-TYPE 3 -- 8010-00-900-2940

=====
Product Identification
=====

Product ID:WHITE TRAFFIC PAINT-TYPE 3

MSDS Date:01/01/1987

FSC:8010

NIIN:00-900-2940

MSDS Number: BFVKK

=== Responsible Party ===

Company Name:CORONADO PAINT CO

Address:308 OLD COUNTY RD

Box:308

City:EDGEWATER

State:FL

ZIP:32032-1812

Country:US

Info Phone Num:904-428-6461 / FAX 904-427-7130

Emer

gency Phone Num:904-428-6461

CAGE:33200

=== Contractor Identification ===

Company Name:CORONADO PAINT COMPANY, INC.

Address:308 OLD COUNTY ROAD

Box:City:EDGEWATER

State:FL

ZIP:32132-1812

Country:US

Phone:904-428-6461

CAGE:33200

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM DISTILLATES (NAPHTHA OR RUBBER SOLVENT)

CAS:8002-05-9

RTECS #:SE7449000

Fraction by Wt: 23.8%

OSHA PEL:400 PPM

ACGIH TLV:400 PPM; 8990

Ingred Name:LEAD NAPHTHENATE

RTECS #:OG2025

000

Fraction by Wt: 0.1%

=====
Hazards Identification
=====

Effects of Overexposure:SEVERE EYE IRRITATION. DRIES SKIN. INHALATION CAUSES HEADACHE,DIZZINESS AND NAUSEA

=====
First Aid Measures
=====

First Aid:EYES-FLUSH WITH WATER.SKIN-WASH WITH MILD SOAP AND WATER;APPLY SKIN CREAM.INHALATION-REMOVE TO FRESH AIR-CALL PHYSICIAN-APPLY ARTIFICIAL RESPIRATION IF NECESSARY

=====
Fire Fighting Measures
=====

Flash Point:22F;-6C SCC

Lower Limits:0.9

Upper Limits:7.0

Extinguishing Media:FOAM,CARBON DIOXIDE,DRY CHEMICAL

Fire Fighting Procedures:TREAT AS CLASS B FIRE

Unusual Fire/Explosion Hazard:VAPORS MAY FORM EXPLOSIVE MIXTURE WITH AIR

=====
Accidental Release Measures
=====

Spill Release Procedures:WEAR RESPIRATOR.FLUSH WITH WATER INTO RETAINING AREA OR CONTAINER.AVOID EXPOSURE TO SPARKS, FIRE OR HOT METAL SURFACES.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS AND OPEN FLME. USE WITH ADEQUATE VENTILATION, AVOID PROLONGED OR REPEATED CONTACT WITH SKIN.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:SELF CONTAINED NIOSH APPROVED PROTECTION IF TLV IS EXCEEDED

Ventilation:LOCAL

Protective Gloves:YES

Other Protective Equipment:EYE BATH AND SAFETY SHOWER

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:169F;76C

Vapor Pres:6

Vapor Density:3.7

Spec Gravity:1.52

Evaporation Rate & Reference:3.8 BUAC

Solubility in Water:SLIGHT

Appearance and Odor:WHITE OPAQUE LIQUID;PETROLEUM DISTILLATE ODOR

Percent Volatiles by Volume:47.1

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HEAT,SPA

RKS, OPEN FLAMES OR FIRE

Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CO

===== Disposal Considerations =====

Waste Disposal Methods:LANDFILL, INCINERATION UNDER SAFE AND SUPERVISED
CONDITIONS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this in-
formation to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.