

CORONADO PAINT CO., INC. -- PAINT, TRAFFIC YELLOW-TYPE I -- 8010-00-900-3648

=====  
Product Identification  
=====

Product ID:PAINT, TRAFFIC YELLOW-TYPE I

MSDS Date:01/01/1987

FSC:8010

NIIN:00-900-3648

MSDS Number: BFVKX

=== Responsible Party ===

Company Name:CORONADO PAINT CO., INC.

Address:308 OLD COUNTY RD

Box:308

City:EDGEWATER

State:FL

ZIP:32032-1812

Country:US

CAGE:33200

=== Contractor Identif

ication ===

Company Name:CORONADO PAINT COMPANY, INC.

Address:308 OLD COUNTY ROAD

Box:City:EDGEWATER

State:FL

ZIP:32132-1812

Country:US

Phone:904-428-6461

CAGE:33200

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ALIPHATIC HYDROCARBONS

Fraction by Wt: 30.6%

Other REC Limits:NONE SPECIFIED

ACGIH TLV:200 PPM

Ingred Name:LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29 CFR 1910.1025)

(CRO3 CEILING 0.1 MG/M3)

CAS:7758-97-6

RTECS #:GB2975000

Fraction by Wt: 7.2%

Other

REC Limits:NONE SPECIFIED  
OSHA PEL:0.05 MG/M3 (PB)  
ACGIH TLV:0.05MG/M3(CR)A2;8990

===== Hazards Identification =====

Health Hazards Acute and Chronic:MAY BE POISONOUS IF INHALED OR ABSORBED THROUGH SKIN. VAPORS MAY CAUSE DIZZINESS OR SUFFOCATION. CONTACT MAY IRRITATE OR BURN SKIN & EYES. FIRE MAY PRODUCE IRRITATING OR POISONOUS GASES. RUNOFF FOR FIRE CONTROL OR DILUTION WATER MAY CAUSE POLLUTION.

Effects of Overexposure:PROLONGED INHALATION:H  
EADACHE, DIZZINESS,  
NAUSEA. SKIN CONTACT:DRY SKIN. SEVERE EYE IRRITATION.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER. SKIN: WASH WITH MILD SOAP & WATER, APPLY SKIN CREAM. INHALATION: REMOVE TO FRESH AIR, CALL A PHYSICIAN. IF NECESSARY, APPLY ARTIFICIAL RESPIRATION.

===== Fire Fighting Measures =====

Flash Point Method:SCC  
Flash Point:57 F/14 C  
Lower Limits:0.9  
Upper Limits:7.0  
Extinguishi  
ng Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL  
Fire Fighting Procedures:TREAT AS CLASS B FIRE.  
Unusual Fire/Explosion Hazard:VAPORS MAY FORM EXPLOSIVE MIXTURE WITH AIR.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR A RESPIRATOR. FLUSH WITH WATER INTO RETAINING AREA OR CONTAINER. AVOID EXPOSURE TO SPARKS, FIRE OR HOT METAL.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY

FROM HEAT, SPARKS & OPEN

FLAME. USE WITH ADEQUATE VENTILATION. AVOID PROLONGED OR REPEATED CONTACT WITH SKIN.

Other Precautions: PERSONS WHO HANDLE THIS PRODUCT REGULARLY SHOULD HAVE PERIODIC BLOOD LEAD DETERMINATIONS.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection: SELF CONTAINED NIOSH APPROVED PROTECTION IF TLV IS EXCEEDED

Ventilation: LOCAL EXHAUST

Protective Gloves: YES

Eye Protection: YES

Other Protective Equipment: EYE BATH & SAFETY SHOWER

Supplemental Safety and Health

=====  
===== Physical/Chemical Properties =====

HCC: F2

Boiling Pt: B.P. Text: 240F, 116C

Vapor Pres: 6

Vapor Density: 3.7

Spec Gravity: 1.35

Evaporation Rate & Reference: 1.2 BUAC

Solubility in Water: SLIGHT

Appearance and Odor: YELLOW OPAQUE LIQUID; PETROLEUM DISTILLATEL-ODOR.

Percent Volatiles by Volume: 55.6

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AG

ENTS

Stability Condition to Avoid: HEAT, SPARKS, OPEN FLAME OR FIRE.

Hazardous Decomposition Products: THERMAL DECOMPOSITION MAY YIELD CARBON MONOXIDE

=====  
===== Disposal Considerations =====

Waste Disposal Methods: LANDFILL, INCINERATION UNDER SAFE & SUPERVISED CONDITION

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no m

anner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.