

PRATT AND LAMBERT INC -- 745614 ENAMEL ALKYD SG GRAY 26152 -- 8010-00-901-1059

=====  
Product Identification  
=====

Product ID:745614 ENAMEL ALKYD SG GRAY 26152

MSDS Date:01/01/1985

FSC:8010

NIIN:00-901-1059

MSDS Number: BFVMN

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency

Phone Num:316-733-1361

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====  
Composition/Information on Ingredients  
=====

Ingred Name:MINERAL SPIRITS

CAS:64475-85-0

RTECS #:PY8240000

Fraction by Wt: 35%

ACGIH TLV:500 PPM

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;91

92

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:SILICA, CRYSTALLINE - CRISTOBALITE

CAS:14464-46-1

RTECS #:VV7325000

OSHA PEL:SEE TABLE Z3

ACGIH TLV:0.05 MG/M3 RDUST9293

Ingred Name:TALC (CONTAINING NO ASBESTOS)

CAS:14807-96-6

RTECS #:WW2710000

OSHA PEL:2 MG/M3 RDUST

ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:VOC. ORGANIC CMPD 3.7 LB/GAL LESS WATER & NPRS\* 444 G/L

LESS WATER VOC. 8.4 LB/GAL SOLIDS 1008 G/L SOLIDS CALCU

RTECS #:9999999VO

=====  
Hazards Identification  
=====

Effects of Overexposure:INHALATION-ANESTHETIC,IRRITATION OF RESPIRATORY TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION.

=====  
First Aid Measures  
=====

First Aid:CONTACT-FLUSH SKIN AND EYES WITH WATER WHILE REMOVING CONTAMINATED CLOTHING. INHALATION-REMOVE TO FRESH AIR. CALL PHYSICIAN IF SYMPTOMS PERSIST.

=====  
Fire Fighting Measures  
=====

Flash Point:104F, 40C TCC

Lower Limits:1.10

Extinguishing Media:NFPA CLASS B EXTINGUISHER; POLYMER FOAM FOR LARGE FIRES

Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS SHOULD BE AVAILABLE

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. VENT

ILATE AREA. REMOVE WITH INERT ABSORBENT AND  
NON-SPARKING TOOLS.

=====  
Handling and Storage

Handling and Storage Precautions:DO NOT STORE ABOVE 120F STORE LARGE  
QUANTITIES IN BUILDING DESIGNED TO COMPLY WITH OSHA 1910.106  
Other Precautions:GROUND CONTAINERS WHEN POURING.AVOID FREE FALL OF  
LIQUID IN XS OF FEW INCHES DO NOT FLAME CUT, BRAZE OR WELD COATER  
MATERIAL WITHOUT BUR OF MINES APPROVED RESPIRATOR OR APPROPRIATE  
VENTILATION

=====  
Exposure Controls/Personal Protection

Respiratory Protection:OPEN AREA:BUR MINES MECH RESPIRATOR;CLOSED:BUR  
MINES CHEM/MECH FILTE  
Ventilation:GENERAL DILUTION OF LOCAL EXHAUST TO KEEP TLV BELOW LIMIT  
Protective Gloves:REG IF LONG CON  
Eye Protection:TO PROTECT VS SPLASHING  
Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO  
CONTAMINATED CLOTHING.  
Supplemental Safety and Health

=====  
Physical/Chemical Properties

HCC:F2  
Boiling Pt:B.P. Text:311-373F  
Vapor Density:ETHER  
Percent Volatiles by Volume:57

=====  
Stability and Reactivity Data

Stability Indicator/Materials to Avoid:YES

=====  
Disposal Considerations

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND  
FEDERAL REGULATIONS-INCINERATE IN APPROVED FACILITY-DO NOT  
INCINERATE CLOSED CONTAINERS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.