

ASHLAND OIL -- TECTYL 846 -- 8030-00-903-0931

=====
Product Identification
=====

Product ID:TECTYL 846

MSDS Date:01/01/1985

FSC:8030

NIIN:00-903-0931

MSDS Number: BFVRQ

=== Responsible Party ===

Company Name:ASHLAND OIL

Address:1409 WINCHESTER AVE

Box:391

City:ASHLAND

State:KY

ZIP:41114

Country:US

CAGE:81355

=== Contractor Identification ===

Company Name:ASHLAND INC

Address:1409 WINCHESTER AVE

Bo

x:391

City:ASHLAND

State:KY

ZIP:41114

Country:US

Phone:800-622-6846

CAGE:81355

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 50.1%

OSHA PEL:100 PPM

Ingred Name:PETROLEUM SULFONATE

Fraction by Wt: 4.5%

Ingred Name:CALCIUM SOAP OF MIXED SYNTHETIC FATTY ACIDS.

Fraction by Wt: 45.4%

=====
Hazards Identification
=====

Effects of Overexposure:

MAY CAUSE IRRITATION; EXCESSIVE INHALATION MAY CAUSE DIZZINESS, NAUSEA, VOMITING, HEADACHE.

=====
First Aid Measures
=====

First Aid:CONTAINS PETROLEUM DISTILLATE.IF SWALLOWED,DO NOT INDUCE VOMITING.OBTAIN MEDICAL ATTENTION.MAY CAUSE IRRITATION;EXCESSIVE INHALATION MAY CAUSE DIZZINESS,NAUSEA,VOMITING,HEADACHE.

=====
Fire Fighting Measures
=====

Flash Point:100 PMCC(MIN)

Lower Limits:1.1

Upper Limits:6.1

Extinguishing Media:CO*2, FOAM, DRY CHEMICAL

Fire Fighting Procedures:NONE-TYPE USED FOR PETROLEUM BASE PRODUCTS.

Unusual Fire/Explosion Hazard:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:NO SPECIAL REQUIREMENTS;DISPOSAL OR CLEAN UP SIMILAR TO PETROLEUM PRODUCTS(ELIMINATE IGNITION SOURCES,CONTAIN BY DIKE,PUMP INTO SALVAGE TANK.

=====
Handling and Storage
=====

Handling and Storage Precautions:HANDLING

-SIMILAR TO CONVENTIONAL

MINERAL SPIRITS.

Other Precautions:NONE

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NONE

Ventilation:ADEQUATE VENT,AS WITH ALL ALIPHATIC SOLVENTS

Protective Gloves:ONLY IN ALLERGY

Eye Protection:SAFETY GLASSES

Other Protective Equipment:NONE

Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:F4

Boiling Pt:B.P. Text:300-365F

Vapor Pres:1-2

Vapor Density:4.75

Evapora

tion Rate & Reference:15 MIN(SPOT DRY)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:FIRM WAXY FILM

Percent Volatiles by Volume:50.1

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:FLAMMABLE-KEEP AWAY FROM OPEN FLAMES&
EXCESSIVE HEAT

Hazardous Decomposition Products:CO*2,SIO*2,CO

===== Disposal Considerations =====

Waste Disposal Met

hods:SIMILAR TO THOSE REQUIRED OF PETROLEUM PRODUCTS
SUCH AS LIQUID INCINERATION ON WITH OFF GAS SCRUBBING

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional
advice to verify and
assume responsibility for the suitability of this information to their
particular situation.