

DYNATRON/BONDO CORP. -- BONDO -- 8010-00-926-2135

=====  
Product Identification  
=====

Product ID:BONDO

MSDS Date:01/01/1987

FSC:8010

NIIN:00-926-2135

Kit Part:Y

MSDS Number: BFWTW

=== Responsible Party ===

Company Name:DYNATRON/BONDO CORP.

Emergency Phone Num:404-351-2730

CAGE:16522

=== Contractor Identification ===

Company Name:BONDO/MAR-HYDE CORP

Address:3700 ATLANTA INDUSTRIAL PKWY NW

Box:City:

ATLANTA

State:GA

ZIP:30331

Country:US

Phone:404-696-2730

CAGE:16522

=====  
Composition/Information on Ingredients  
=====

Ingred Name:TITANIUM DIOXIDE

Ingred Name:STYRENE MONOMER

ACGIH TLV:100 PPM

Ingred Name:ANILINE (SARA III)

CAS:62-53-3

RTECS #:BW6650000

OSHA PEL:S, 5 PPM

ACGIH TLV:S, 2 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

=====  
Hazards Identification  
=====

Effects of Overexposure:EYE/SKIN IRRITATION; RESPIRATORY TRACT

# IRRITATION

## ===== First Aid Measures =====

First Aid:WASH SKIN WITH SOAP AND WATER; FLUSH EYES WITH WATER 15 MINUTES; CALL DOCTOR; REMOVE TO FRESH AIR

## ===== Fire Fighting Measures =====

Flash Point:100F,37.8C TOC

Lower Limits:1.1

Upper Limits:6.1

Extinguishing Media:WATER,CARBON DIOXIDE,FOAM SODIUM BICARBONATE

Fire Fighting Procedures:VENT SMOKE; USE GAS MASK OR REMATE AIR SUPPLY

## ===== Accidental Release Measures =====

Spill Release Procedures:SHOVELING AND WIPING

## ===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE AT HIGH TEMPERATURES

## ===== Exposure Controls/Personal Protection =====

Respiratory Protection:ADEQUATE VENTILATION

Ventilation:LOCAL EXHAUST

Eye Protection:RECOMMENDED

Supplemental Safety and Health

2 PART KIT; POLYESTER RESIN 40 PERCENT; MAGNESIUM/SILICATE 59 PERCENT;  
PIGMENT 1 PERCENT

PERCENT

## ===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:295F,146.1C

Vapor Pres:7.0

Vapor Density:3.6

Spec Gravity:1.79

Evaporation Rate & Reference:4.9, BUTYLACETATE

Solubility in Water:SLIGHT

Appearance and Odor:GRAY,VISCOUS COMPOUND, PUNGENT ODOR

Percent Volatiles by Volume:16.0

## ===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ORGANIC PEROXIDES

Stability Condition to Avoid:EXPOS

URE TO IGNITION SOURCES IN CONFINED  
AREAS

Hazardous Decomposition Products:STYRENE VAPORS

Conditions to Avoid Polymerization:CONTACT WITH ORGANIC PEROXIDES

===== Disposal Considerations =====

Waste Disposal Methods:APPROVED LANDFILL

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or impl  
ied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.