EASTMAN KODAK COMPANY --187 3256 VNF-1/RVNP STOP BATH AND REPLENISHER, CONCENTRATE -- 6750-00-926-5201 Product ID:187 3256 VNF-1/RVNP STOP BATH AND REPLENISHER, CONCENTRATE MSDS Date:08/28/1997 FSC:6750 NIIN:00-926-5201 MSDS Number: BFWWC === Responsible Party === Company Name: EASTMAN KODAK COMPANY Address:343 STATE STREET City:ROCHESTER State:NY ZIP:14650 Countr y:US Info Phone Num:800-242-2424 Emergency Phone Num:716-722-5151 CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139 Company Name: EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES Address:800 LEE RD Box:City:ROCHESTER State:NY ZIP:14650-3129 Country:US Phone:800-828-6203 CAGE:5K871

View NSN Online: https://aerobasegroup.com/nsn/6750-00-926-5201

======= Composition/Information

on Ingredients =========

Ingred Name:ACETIC ACID (CERCLA) CAS:64-19-7 RTECS #:AF1225000 Fraction by Wt: 70 - 75% Other REC Limits:NONE RECOMMENDED OSHA PEL:10 PPM ACGIH TLV:10 PPM/15 STEL; 9596 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 20 - 25% Other REC Limits:NONE RECOMMENDED OSHA PEL:NOT RELEVANT ACGIH TLV:NOT RELEVANT

Ingred Name:SODIUM ACETATE CAS:127-09-3 RTECS #:AJ4300010 Fraction by Wt: 5 - 10% Other REC Limits:NON E RECOMMENDED

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS UNKNOWN. Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Explanation of Carcinogenicity:NONE Effects of Overexposure:SEVERE IRRITATION, TEARING, NAUSEA, VOMITING, SEVERE BURNS, PAIN Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN

DISORDERS, EYE PROBLEMS OR IMPAIRED RESPIRATORY FUNCTION MA Y BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT.

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES:FLUSH WITH WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. CALL PHYSICIAN. SKIN:WASH WITH SOAP & WATER. O RAL:DO NOT INDUCE VOMITING. IF CONSCIOUS, DRINK A GLASS OF WATER. GET MEDICAL ATTENTION IMMEDIATELY. NEVER GIVE ANYTIHING BY MOUTH TO AN UNC ONSCIOUS PERSON.

Flash Point:NONE Lower Limits:NOT RELEVANT Upper Limits:NOT RELEVANT Extinguishing Media:USE WATER SPRAY, CARBON DIOXIDE (CO2), ALCOHOL FOAM OR DRY CHEMICAL. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS. Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS. HAZARDOUS DECOMPOSITION PRODUCTS MAY BE FORMED. Unusual Fire/Explosion Hazard:CONTAINER MAY BURST.

Spill Release Procedures: ELIMINATE ALL SOURCES OF IGNITION. FLUSH TO SEWER WITH LARGE AMOUNT OF WATER. OTHERWISE, ABSORB SPILL WITH INERT MATERIAL SUCH AS VERMICULITE, THEN PLACE IN A CONTAINER FOR CHEMICAL WASTE. CLEAN SURFA CE THOROUGHLY TO REMOVE RESIDUAL CONTAMINATION. Neutralizing Agent: BASE

Handling and Storage Precautions:ST
ORE IN COOL, VENTILATED PLACE, AWAY
FROM INCOMPATIBLE MATERIALS. KEEP CONTAINER TIGHTLY CLOSED.
Other Precautions:CORROSIVE. EMPTY CONTAINERS RETAIN RESIDUE. FOLLOW
ALL LABEL INSTRUCTIONS. KEEP OUT OF REACH OF CHILDREN. AVOID
BREATHING VAPORS. DO NOT GET IN EYE, ON SKIN OR ON CLOTHING. DO NOT INGEST.

Respiratory Protection: IF ENGINEERING CONTROLS DO NOT MAINTAIN AIRBORNE CONCENTRATIONS TO AN ACCEPTABLE LEVE

L, A NIOSH-APPROVED ORGANIC

VAPOR, ACID GAS RESPIRATOR MUST BE WORN.

Ventilation: GOOD GENERAL VENTILATION (TYPICALLY 10 AIR CHANGES/HR) SHOULD BE USED. VENTILATION RATES SHOULD BE MATCHED TO CONDITIONS Protective Gloves: RUBBER

Eye Protection: SAFETY GLASSES WITH SIDE SHIELD/GOGGLES Other Protective Equipment: EYE BATH, WASHING FACILITIES, SAFETY SHOWER

Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. WASH THOROUGHLY BEFORE EATING, DRINKI NG/SMOKING. Supplemental Safety and Health ECOLOGICAL INFORMATION: A HIGH BIOCHEMICAL OXYGEN DEMAND, A LOW POTENTIAL TO AFFECT AQUATIC ORGANISMS. AFTER DILUTION WITH LARGE AMOUNT OF WATER, THIS MATERIAL IS NOT EXPECTED TO CAUSE ADVERSE ENVIRON MENTAL EFFECTS.

HCC:C2 NRC/State Lic Num:NOT RELEVANT Boiling Pt:=100.C, 212.F Vapor Pres:18 @ 68F Vapor Density:0.6 Spec Gravity:1.10 pH:3.5 Solubility in Water:COMPLETE Ap pearance and Odor:COLORLESS LIQUID - VINEGAR ODOR Percent Volatiles by Volume:90- 95

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS, BASES, AMINES, METALS Stability Condition to Avoid:TEMPERATURES ABOVE 120F/49C Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL IS SUBJ ECT TO

FEDERAL, STATE OR LOCAL REGULATIONS. FLUSH TO SEWER WITH LARGE AMOUNT OF WATER, IF ALLOWED. SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE, FOLLOW LABEL WARNINGS EVEN AFTER CONTAINER IS EMPTIED.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.