

EASTMAN KODAK COMPANY -- 187 3256 VNF-1/RVNP STOP BATH AND  
REPLENISHER,CONCENTRATE -- 6750-00-926-5201

===== Product Identification =====

Product ID:187 3256 VNF-1/RVNP STOP BATH AND REPLENISHER,CONCENTRATE

MSDS Date:08/28/1997

FSC:6750

NIIN:00-926-5201

MSDS Number: BFWWC

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Countr

y:US

Info Phone Num:800-242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

===== Composition/Information

on Ingredients =====

Ingred Name:ACETIC ACID (CERCLA)  
CAS:64-19-7  
RTECS #:AF1225000  
Fraction by Wt: 70 - 75%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:10 PPM  
ACGIH TLV:10 PPM/15 STEL; 9596  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:WATER  
CAS:7732-18-5  
RTECS #:ZC0110000  
Fraction by Wt: 20 - 25%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:NOT RELEVANT  
ACGIH TLV:NOT RELEVANT

Ingred Name:SODIUM ACETATE  
CAS:127-09-3  
RTECS #:AJ4300010  
Fraction by Wt: 5 - 10%  
Other REC Limits:NON  
E RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS UNKNOWN.  
Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Explanation of Carcinogenicity:NONE  
Effects of Overexposure:SEVERE IRRITATION, TEARING, NAUSEA, VOMITING,  
SEVERE BURNS, PAIN  
Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN  
DISORDERS, EYE PROBLEMS OR IMPAIRED RESPIRATORY FUNCTION MA  
Y BE  
MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT.

===== First Aid Measures =====

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:REMOVE TO FRESH  
AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES:FLUSH WITH WATER FOR 15  
MINUTES. HOLD EYELIDS OPEN. CALL PHYSICIAN. SKIN:WASH WITH SOAP &  
WATER. O RAL:DO NOT INDUCE VOMITING. IF CONSCIOUS, DRINK A GLASS OF  
WATER. GET MEDICAL ATTENTION IMMEDIATELY. NEVER GIVE ANYTIHING BY  
MOUTH TO AN UNC

UNCONSCIOUS PERSON.

===== Fire Fighting Measures =====

Flash Point:NONE

Lower Limits:NOT RELEVANT

Upper Limits:NOT RELEVANT

Extinguishing Media:USE WATER SPRAY, CARBON DIOXIDE (CO2), ALCOHOL FOAM OR DRY CHEMICAL. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS. HAZARDOUS DECOMPOSITION PRODUCTS MAY BE FORMED.

Unusual Fire/Explosion Hazard:CONTAINER MAY BURST.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. FLUSH TO SEWER WITH LARGE AMOUNT OF WATER. OTHERWISE, ABSORB SPILL WITH INERT MATERIAL SUCH AS VERMICULITE, THEN PLACE IN A CONTAINER FOR CHEMICAL WASTE. CLEAN SURFACE THOROUGHLY TO REMOVE RESIDUAL CONTAMINATION.

Neutralizing Agent:BASE

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, VENTILATED PLACE, AWAY FROM INCOMPATIBLE MATERIALS. KEEP CONTAINER TIGHTLY CLOSED.

Other Precautions:CORROSIVE. EMPTY CONTAINERS RETAIN RESIDUE. FOLLOW ALL LABEL INSTRUCTIONS. KEEP OUT OF REACH OF CHILDREN. AVOID BREATHING VAPORS. DO NOT GET IN EYE, ON SKIN OR ON CLOTHING. DO NOT INGEST.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF ENGINEERING CONTROLS DO NOT MAINTAIN AIRBORNE CONCENTRATIONS TO AN ACCEPTABLE LEVEL,

A NIOSH-APPROVED ORGANIC VAPOR, ACID GAS RESPIRATOR MUST BE WORN.

Ventilation:GOOD GENERAL VENTILATION (TYPICALLY 10 AIR CHANGES/HR) SHOULD BE USED. VENTILATION RATES SHOULD BE MATCHED TO CONDITIONS

Protective Gloves:RUBBER

Eye Protection:SAFETY GLASSES WITH SIDE SHIELD/GOGGLES

Other Protective Equipment:EYE BATH, WASHING FACILITIES, SAFETY SHOWER

Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. WASH THOROUGHLY BEFORE EATING, DRINKING

NG/SMOKING.

Supplemental Safety and Health

ECOLOGICAL INFORMATION: A HIGH BIOCHEMICAL OXYGEN DEMAND, A LOW POTENTIAL TO AFFECT AQUATIC ORGANISMS. AFTER DILUTION WITH LARGE AMOUNT OF WATER, THIS MATERIAL IS NOT EXPECTED TO CAUSE ADVERSE ENVIRONMENTAL EFFECTS.

===== Physical/Chemical Properties =====

HCC:C2

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:=100.C, 212.F

Vapor Pres:18 @ 68F

Vapor Density:0.6

Spec Gravity:1.10

pH:3.5

Solubility in Water:COMPLETE

Appearance and Odor:COLORLESS LIQUID - VINEGAR ODOR

Percent Volatiles by Volume:90- 95

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, BASES, AMINES, METALS

Stability Condition to Avoid:TEMPERATURES ABOVE 120F/49C

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL IS SUBJECT TO

FEDERAL, STATE OR LOCAL REGULATIONS. FLUSH TO SEWER WITH LARGE AMOUNT OF WATER, IF ALLOWED. SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE, FOLLOW LABEL WARNINGS EVEN AFTER CONTAINER IS EMPTIED.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.