View NSN Online: https://aerobasegroup.com/nsn/6850-00-926-5298

CHEMICAL COMMODITIES AGENCY, INC. -- CORROSION REMOVING COMPOUND

6850-00-926-5298

Product ID:CORROSION REMOVING COMPOUND

MSDS Date:01/01/1985

FSC:6850

NIIN:00-926-5298

MSDS Number: BFWWM === Responsible Party ===

Company Name: CHEMICAL COMMODITIES AGENCY, INC.

Address:27447 PACIFIC STREET

City:HIGHLAND

State:CA

ZIP:92346-2640

Country:US

Info Phone Num:714-864-23

10

Emergency Phone Num:714-864-2310

CAGE:60777

=== Contractor Identification ===

Company Name: CHEMICAL COMMODITIES AGENCY, INC.

Address:27447 PACIFIC STREET

Box:City:HIGHLAND

State:CA

ZIP:92346-2640

Country:US

Phone:909-864-2310

CAGE:60777

======= Composition/Information on Ingredients ========

Ingred Name:PHOSPHORIC ACID (SARA III)

CAS:7664-38-2

RTECS #:TB6300000 Fraction by Wt: 5.0%

OSHA PEL:1 MG/M3/3 STEL

ACGIH TLV:1 MG/M3/3 STEL; 9192

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Fraction by Wt: 65% **ACGIH TLV:100 PPM** Ingred Name: METHYLENE CHLORIDE (SARA III) CAS:75-09-2 RTECS #:PA8050000 Fraction by Wt: 20.0% OSHA PEL:500 PPM/C,1000; Z2 ACGIH TLV:50 PPM, A2; 9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS ============= Hazards Identification ======================== Effects of Overexposure: DIZZINESS. EXTREME EYE IRRITATION. MAY DEFAT SKIN ON PROLONGED CONTACT. ========== First Aid Measures ========= ======== First Aid: INHALATION, REMOVE TO FRESH AIR. EYE CONTACT FLOOD WITH WATER-SEE MEDICAL ATTENTION. SKIN CONTACT, FLUSH WELL WITH WATER. ============ Fire Fighting Measures ========================= Flash Point:149F TOC,185 TCC Lower Limits:6.0 Upper Limits: 1.0 Fire Fighting Procedures: NONE ========= Accidental Release Measures ============== Spill Release Procedures:WIPE UP OR FLUSH WITH WATER. ============= Handling and Storage ========================== Handling and Storage Precautions: STORE IN COOL, DRY PLACE.DO NOT USE AROUND OPEN FLAME. ====== Exposure Controls/Personal Protection ======== Respiratory Protection: CARTRIDGE TYPE IN AREAS OF HIGH MIST OR VAPOR CONCENTRATION Ventilation: MECHANICAL TYPE IS PREFERRED. Protective Gloves: SOLVENT RESIST. Eye Protection: FACE SHIELD OR GOGGLES Supplemental Safety and Health PERCENTAGE COMPOSITIONS OF ITEMS SHOWN ARE THE MAX9MUM ONES ======== Physical/Chemical Prop

Ingred Name: AROMATIC PETROLEUM SOLVENTS

| erties ==========   |
|---|
| HCC:C1 Boiling Pt:B.P. Text:356F Vapor Pres:37 Vapor Density:1.0 Spec Gravity:0.97 Evaporation Rate & DITYL ACETATE->1.0 Solubility in Water:NEGLIGIBLE Appearance and Odor:CLEAR,REDDISH BROWN LIQUID WITH SOLVENT ODOR Percent Volatiles by Volume:80 |
| ========= Stability and Reactivity Data =========   |
| Stability Indicator/Materials to Avoid:YES STRONG CAUSTIC MATERIALS. Stability Condition to Avoid:TEMPERATURES ABOVE 104 F Hazardous Decompo sition Products:PHOSGENE ON DIRECT CONTACT WITH FLAME  |
| ======== Disposal Considerations ==========   |
| Waste Disposal Methods:LAND FILL OR EVAPORATE   |

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person u tilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.