View NSN Online: https://aerobasegroup.com/nsn/8040-00-929-4620

PRODUCTS RESEARCH AND CHEMICAL CORP. -- PR-1902 -- 8040-00-929-4620

Product ID:PR-1902 MSDS Date:01/01/1985

FSC:8040

NIIN:00-929-4620

MSDS Number: BFXCD === Responsible Party ===

Company Name: PRODUCTS RESEARCH AND CHEMICAL CORP.

Address:5430 SAN FERNANDO ROAD

Box:1800

City:GLENDALE

State:CA ZIP:91209 Country:US

Info Phone Num:818-240-2060 Emergency Phone Num:818

-240-2060

CAGE:DO563

=== Contractor Identification ===

Company Name: PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA ZIP:91209 Country:US

Phone:818-240-2060

CAGE:83574

Company Name: PRODUCTS RESEARCH & CHEMICAL

Address: NOW DBA COURTAULDS AEROSPACE

Box:1800

City:GLENDALE

State:CA ZIP:91209

Phone:818-240-2060

CAGE:DO563

====== Composition/Information on Ingredients ========

Ingred Name: ISOPROPYL ALCOHOL (SARA III)

Ingred Name: ACETONE (SARA III) CAS:67-64-1 RTECS #:AL3150000 Fraction by Wt: 28% OSHA PEL:1000PPM ACGIH TLV:750PPM/1000STEL:9293 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Effects of Overexposure: EYE, THROAT, SKIN, LUNG IRRITANT, HEADACHE, NAUSEA First Ai d:WASH SKIN THROUGHLY FLUSH EYES WITH WATER, REMOVE TO FRESH AIR, REMOVE CONTAMINATED CLOTHING GIVE ARTIFICIAL RESPIRATION IF NEEDED, CALL DOCTOR Flash Point:50F/10C CC Lower Limits:2.0 Upper Limits:12.0 Extinguishing Media: FOAM, DRY CHEMICAL, CARBON DIOXIDE Fire Fighting Procedures: WEAR SELF-CNTND BRTHG APPARATUS. WATER MAY BE **INEFFECTIVE** Unusual Fire/Explosion Hazard: MAY BE IGNITED BY HEAT, FLAMES, SPARKS. CONT MAY E XPLODE IN HEAT OF FIRE.EXTREMELY FLAMMABLE. ======== Accidental Release Measures =========== Spill Release Procedures: VENTILATE AREA MECHANICALLY, KEEP FROM FLAME, FIRE, SPARKS, IGNITION SOURCES; DO NOT BREATHE VAPORS; CLEAN UP WITH ABSORBENT MATERIAL, RAGS AND PAPER TOWELS =========== Handling and Storage ============================ Handling and Storage Precautions: KEEP FROM HEAT, SPARKS, FIRE, SOURCES OF IGNITION; AVOID STORAGE IN DIRECT SUNLIGHT; AVOID PROLONGE

CAS:67-63-0

RTECS #:NT8050000 Fraction by Wt: 28%

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

D SKIN CONTACT; STORE CONTAINERS CLOSED AND UPRIGHT. Other Precautions: STORE IN COOL, DRY PLACE ===== Exposure Controls/Personal Protection ======== Respiratory Protection: SELF-CNTND-BRTHG APP, BUT NOT REQUIRED IF VENTILATION IS ADEQUATE. Ventilation: MECHANICAL/LOCAL EXHAUST ADEQUATE TO MINIMIZE VAPORS Protective Gloves: POLYETHYLENE Eye Protection: GOGGLES/FACE SHIELD Other Protective Equipment: NEAR IMPERVIOUS CLOTHING/BOOTS. Supplemental Safety and Health ============ = Physical/Chemical Properties ========= Boiling Pt:B.P. Text:134F Vapor Pres:60 Vapor Density:2.0 Spec Gravity:0.85 Evaporation Rate & Dr. Reference: 7.7, BUTYL ACETATE Solubility in Water:SLIGHT Appearance and Odor:LIGHT BLUE LIQUID ALCOHOL ODOR. Percent Volatiles by Volume:UNK ======== Stability and Reactivity Data =========== Stability Indicator/Materials to Avoid:YES AVOID STRONG ACIDS, OXIDIZERS, ALKALI. Stability Condition to Avoid: IGNITION SOURCES Hazardous Dec omposition Products: VARIOUS HYDRO CARBONS, CO, CO*2 ======= Disposal Considerations ============

Waste Disposal Methods:PLACE IN CLOSED CONTAINERS AND DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever. expressly or implied, wa

rrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.