

FISKE BROS REFINING CO -- LUBRIPLATE #630-2 -- 9150-00-929-7946

=====
Product Identification
=====

Product ID:LUBRIPLATE #630-2

MSDS Date:06/01/1989

FSC:9150

NIIN:00-929-7946

MSDS Number: BFXCP

=== Responsible Party ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Info Phone Num:201-589-9150

Emergency Phone Num:201-589-9150

Preparer's

Name:ROBERT J. SIBILIA

CAGE:73219

=== Contractor Identification ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

Box:City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Phone:201-589-9150

CAGE:73219

=====
Composition/Information on Ingredients
=====

Ingred Name:LITHIUM SOAP

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY8030000

Other REC Limits:5MG/CUM

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:SELECTED ADDITIVE

(CONTAINS SMALL AMOUNT OF ZNO,SEE
INGREDIENT #4)

Ingred Name:ZINC OXIDE

CAS:1314-13-2

RTECS #:ZH4810000

OSHA PEL:15MG/M3 TDUST/5 FUME

ACGIH TLV:10MG/M3 TDUST; 9293

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:UNKNOWN Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE:MILD IRRITATION OF SKIN OR EYES.

CHRONIC:NO DATA AVAILABLE.

Explanation of Carcinogenicity:NONE OF THE I

NGREDIENTS IN THIS PRODUCT

IS LISTED BY NTP, IARC OR OSHA AS A CARCINOGEN.

Effects of Overexposure:SKIN OR EYE CONTACT MAY CAUSE IRRITATION.

INHALED:ONLY LIKELY HAZARD IS ASPIRATION OF LIQUID DURING INGESTION
OR VOMITING.

Medical Cond Aggravated by Exposure:NO DATA AVAILABLE.

=====
First Aid Measures
=====

First Aid:EYES: FLUSH WITH PLENTY OF WATER FOR 15 MINUTES. IF
IRRITATION PERSISTS, SEE DOCTOR. SKIN: WASH WITH SOAP AND WATER
WHILE

REMOVING CONTAMINATED CLOTHING AND SHOES. *** ACCIDENTAL
INJECTION INTO SKIN: SEE DOCTOR IMMEDIATELY. THIS IS A SERIOUS
EMERGENCY ***. INHALATION: REMOVE VICTIM TO FRESH AIR. GIVE
OXYGEN/CPR IF NEEDED. SEE DOCTOR. INGESTION: DO NOT INDUCE
VOMITING. SEE DOCTOR IMMEDIATELY.

=====
Fire Fighting Measures
=====

Flash Point Method:COC

Flash Point:400F/204C

Lower Limits:0.9

Upper Limits:7.0

Extinguishing Media:USE WATER FOG, WATER SPRAY, CARBON DIOXI

DE, FOAM,
OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS IN ENCLOSED AREA.
COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS.
DO NOT CUT, DRILL, GRIND OR WELD, AS THEY MAY EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP GREASE. CLEAN AREA WITH SUITABLE
PETROL
EUM SOLVENT AND INERT ABSORBANT.KEEP OUT OF SEWERS & WATER
COURSES.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN
USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME, OR STRONG
OXIDANTS.

Other Precautions:REMOVE OIL-SOAKED CLOTHING AND LAUNDRER BEFORE REUSE.
CLEANSE SKIN THOROUGHLY AFTER CONTACT. EMPTY CONTAINERS RETAIN
RESIDUE. TREAT THEM AS IF THEY WERE FULL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. NIOSH/MSHA-APPROVED
RESPIRATOR OR SCBA AS APPROPRIATE FOR EXPOSURE OF CONCERN.

Ventilation:MECHANICAL (GENERAL) VENTILATION OR LOCAL EXHAUST
VENTILATION TO KEEP EXPOSURE LEVELS BELOW PEL.

Protective Gloves:NITRILE GLOVES.

Eye Protection:CHEMICAL SAFETY GOGGLES.

Other Protective Equipment:OIL RESISTANT APRON FOR HIGH SPLASH HAZARD
TASKS.

Work Hygienic Practices:WASH THOR
OUGHLY AFTER HANDLING AND BEFORE
EATING. LAUNDRER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health
NONE.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>550F,>288C

Vapor Pres:5

Spec Gravity:0.945

Evaporation Rate & Reference: