

DEVOE & RAYNOLDS CO., INC. -- DR039-CONCENTRATE -- 8010-00-935-7079

=====
Product Identification
=====

Product ID:DR039-CONCENTRATE

MSDS Date:01/01/1987

FSC:8010

NIIN:00-935-7079

MSDS Number: BFXWM

=== Responsible Party ===

Company Name:DEVOE & RAYNOLDS CO., INC.

Emergency Phone Num:714-686-6930

CAGE:EO559

=== Contractor Identification ===

Company Name:DEVOE & RAYNOLDS CO, INC.

Box:7600

CAGE:EO55

9

Company Name:DEVOE COATINGS CO DIV OF GROW GROUP INC

Address:2625 DURAHART ST

Box:City:RIVERSIDE

State:CA

ZIP:92507-2606

Country:US

CAGE:70506

=====
Composition/Information on Ingredients
=====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 24.0%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 29.0%

OSH

A PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:2-BUTOXYETHANOL
CAS:111-76-2
RTECS #:KJ8575000
Fraction by Wt: 7.0%
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9293

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 19.0%
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)
CAS:108-10-1
RT
ECS #:SA9275000
OSHA PEL:100 PPM/75 STEL
ACGIH TLV:50 PPM/75 STEL; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====

Effects of Overexposure:INHALATION-HEADACHE, NAUSEA, DIZZINESS. SKIN CONTACT-MAY CAUSE SKIN IRRITATION IF PROLONGED.

=====
===== First Aid Measures =====

First Aid:INHALATION: MOVE TO FRESH AIR. SKIN: FLUSH WITH LARGE AMOUNTS OF WATER. REMOVE CONTAMINATED CLOTHING. EYE CONTACT: FLUSH WITH CLEAN WATER FOR AT LEAST 15 MIN.-CALL PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point:43F;6.1C PMCC
Extinguishing Media:CO*2, DRY CHEMICAL, FOAM
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:WATER SHOULD BE USED TO COOL CONTAINERS EXPOSED TO FIRE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:AVOID BREATHING VAPORS; EXTINGUISH I

IGNITION

SOURCES IN IMMEDIATE AREA. AVOID CONTACT WITH LIQUID.

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT STORE AT ELEVATED TEMPERATURES.
Other Precautions:CLOSE CONTAINERS AFTER USE.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:U.S. BUR. MINES APPROVED RESPIRATOR IN CONFINED AREAS

Ventilation:SUFFICIENT TO KEEP CONCENTRATION BELOW GIVEN TLV.

Protective Gloves:PROLONGED USE

E

Eye Protection:SOLVENT RESISTANT

Other Protective Equipment:NORMAL PROTECTIVE CLOTHING.

Supplemental Safety and Health

BOILING POINT: 80-173C

=====
Physical/Chemical Properties
=====

HCC:V3

Boiling Pt:B.P. Text:176-343F

Vapor Density:>1

Spec Gravity:1.04

Evaporation Rate & Reference:< ETHER

Solubility in Water:SLIGHT

Appearance and Odor:BLACK-MOBILE LIQUID CONTAINING VOLATILE SOLVENTS.

Percent Volatiles by Volume:82.9

=====
Stability and Reactivity

Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING MATERIALS; SOFTENS RUBBER.

Stability Condition to Avoid:NA

Hazardous Decomposition Products:CO; CO*2

=====
Disposal Considerations
=====

Waste Disposal Methods:DISPOSE OF IN CLOSED CONTAINERS-AWAY FROM
IGNITION SOURCES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The Uni

ted States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.