

GRAPHITE PRODUCTS CORPORATION -- LS-1774 -- 9150-00-943-6880

=====  
Product Identification  
=====

Product ID:LS-1774

MSDS Date:05/04/1987

FSC:9150

NIIN:00-943-6880

MSDS Number: BFYMD

=== Responsible Party ===

Company Name:GRAPHITE PRODUCTS CORPORATION

Address:5756 SHARON-WARREN ROAD

Box:207

City:BROOKFIELD

State:OH

ZIP:44403-9507

Country:US

Info Phone Num:216-394-1617

Emergency Phone Num:216-394-16

17

Preparer's Name:ROBERT RAY HARTSOUGH

CAGE:60218

=== Contractor Identification ===

Company Name:GRAPHITE PRODUCTS CORP

Address:5756 SHARON-WARREN RD

Box:207

City:BROOKFIELD

State:OH

ZIP:44403-9507

Country:US

Phone:216-394-1617

CAGE:60218

=====  
Composition/Information on Ingredients  
=====

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY8030000

Fraction by Wt: 35.0%

Other REC Limits:5MG/CUM(AS OIL MIST)

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3/10

STEL;9192

Ingred Name:MOLYBDENUM DISULFIDE

CAS:1317-33-5

RTECS #:QA4697000

Fraction by Wt: 65.0%

OSHA PEL:10 MG/M3 TDUST (MO)

ACGIH TLV:10 MG/M3 (MO); 8990

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:ACUTE:MAY IRRITATE EYES,SKIN OR  
RESPIRATORY TRACT. CHRONIC:IRRITATION OF SKIN OR DERMATITIS.

Effects of Overexposure:EYE IRRITANT,SKIN IRRITATION OR RESPIRATORY  
TRACT IRRITAT

ION;DERMATITIS ON PROLONGED EXPOSURE.

Medical Cond Aggravated by Exposure:SKIN DISORDERS MAY BE AGGRAVATED.

=====  
First Aid Measures  
=====

First Aid:EYES:FLUSH WITH WATER FOR 15 MINUTES AND CALL A DOCTOR.

SKIN:WASH WITH SOAP AND WATER. INHALATION:REMOVE TO FRESH AIR.

=====  
Fire Fighting Measures  
=====

Flash Point Method:COC

Flash Point:430F/221C

Extinguishing Media:FOAM,CO\*2,DRY CHEMICAL

Fire Fighting Procedures:USE

NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED  
AREA.

Unusual Fire/Explosion Hazard:COMBUSTION OF MOS\*2 CAN PRODUCE OXIDES OF  
SULFUR.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;SCOOP UP AS  
MUCH AS POSSIBLE;USE INERT ABSORBENT MATERIAL AND RECOVER FOR  
PROPER DISPOSAL.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:KEEP IN COOL,DRY AND WELL VENTILATED

AREA.KEEP AWAY FROM HEAT,OPEN FLAME OR IGNITION SOURCES.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NEEDED IF THERE IS ADEQUATE VENTILATION.

Ventilation:GENERAL/LOCAL TO MAINTAIN ADEQUATE VENTILATION.

Protective Gloves:OIL RESISTANT GLOVES

Eye Protection:CHEMICAL GOGGLES

Other Protective Equipment:APRON;FULL EYES OR SKIN PROTECTION.

Work Hygienic Practices:AVOID CONTACT WITH EYES OR SKIN.

Supplemental Safety and Health

MSDS RECEIVED BY DGS

C-SLM:23 FEB 1988.

=====  
===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>600F/316C

Vapor Pres: