

DOW CORNING CORPORATION -- MOLYKOTE G-M PASTE,ORGANIC BASE GREASE --  
9150-00-943-6880

=====  
===== Product Identification =====

Product ID:MOLYKOTE G-M PASTE,ORGANIC BASE GREASE

MSDS Date:01/01/1987

FSC:9150

NIIN:00-943-6880

MSDS Number: BFYMF

=== Responsible Party ===

Company Name:DOW CORNING CORPORATION

Emergency Phone Num:(517) 496-5900

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CO

RNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

=====  
===== Composition/Information on Ingredients =====

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY8030000

Fraction by Wt: 50%

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:MOLYBDENUM DISULFIDE

CAS:1317-33-5

RTECS #:QA4697000

Fraction by Wt: 17%

OSHA PEL:10 MG/M3 TDUST (MO)

ACGIH TLV:10 MG/M3 (MO); 8990

Ingred Name:ZINC PHOSPHATE

Fraction by Wt: 15%

Ingred Name:CALCIUM PHOSPHATE

Fraction by Wt: 15%

Ingred Name:WAX

CAS:8002-74-2

RTECS #:RV0350000

Fraction by Wt: 3%

===== Hazards Identification =====

Effects of Overexposure:IRRIT EYES

===== First Aid Measures =====

First Aid:EY

E: IMMED FLUSH W/WATER AT LEAST 15 MIN.

===== Fire Fighting Measures =====

Flash Point:>250F/121C OC

Extinguishing Media:CO\*2, FOAM

Fire Fighting Procedures:SELF-CNTND BRTNG APPARATUS & PROT CLOTHING

Unusual Fire/Explosion Hazard:NONE KNOWN TO MFR

===== Accidental Release Measures =====

Spill Release Procedures:USE ABSORBENT MATL TO COLLECT & CONTAIN FOR  
SALVAGE OR DISPOSAL

===== Exposure Controls/Personal Protectio

n =====

Respiratory Protection:MFR SUGGESTS NONE SHOULD BE NEEDED

Ventilation:MECH REC

Eye Protection:SAFETY GLASSES

Supplemental Safety and Health

VAP PRESS