View NSN Online: https://aerobasegroup.com/nsn/6810-00-949-0257

Product ID:NORMAL HEXANE MSDS Date:01/01/1985 FSC:6810 NIIN:00-949-0257 **MSDS Number: BFYTQ** === Responsible Party === Company Name: BURDICK & JACKSON LAB, INC (SEE SUP DATA) Address: 1953 S HARVEY STREET City:MUSKEGON State:MI ZIP:49442-6101 Country:US Info Phone Num:616-726-3171 Emergency Phone Num:616-726-3171 CAGE:BURDI === Contractor Identification === Company Name: BURDICK & JACKSON, INC. Address:1953 S. HARVEY STREET Box:City:MUSKEGON State:MI ZIP:49442 Country:US Phone:616-726-3171 CAGE:BURDI Company Name: HONEYWELL, BURDICK AND JACKSON Address: 1953 S HARVEY STREET Box:City:MUSKEGON State:MI ZIP:49442-6101 Country:US Phone:800-368-0050/800-707-4555 CAGE:2H215

Ingred Name:HEXANE (N-HEXANE) CAS:110-54-3 RTE

CS #:MN9275000 OSHA PEL:500 PPM ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB
Ingred Name:METHYLCYCLOPENTANE CAS:96-37-7 RTECS #:GY4640000 Fraction by Wt: 10% ACGIH TLV:500 PPM (MFR)
======================================
Effects of Overexposure:EYE/SKIN: IRRITATION. VAPOR: DIZZY,NAUSEA,EXHILIRATION,MUSCULAR INCOORD,STUPOR,UNCONSCIOUSNESS.
======================================
First Aid:EYE: FLUSH WITH WATER 15 MIN. SKIN: WASH WITH SOAP & WATER,APPLY EMMOLIENT CREAM. INHALATION: REMOVE FROM EXPOSURE,GIVE ARTIFICAL RESPIRATION IF NEEDED,GET MEDICAL ATTN. INGESTION:DO NOT INDUCE VOMITI NG,GET MEDICAL ASSISTANCE.
======================================
Flash Point:-10F/-23C (TCT) Lower Limits:1.2 Upper Limits:7.7 Extinguishing Media:DRY CHEMICAL,CO*2 Fire Fighting Procedures:WATER SPRAY TO COOL EXPOSED CONTAINERS. Unusual Fire/Explosion Hazard:WATER MAY BE INEFFECTIV E.
======================================
Spill Release Procedures: SECURE IGNITION SOURCES, ABSORB IN EARTH OR SAWDUST. WEAR APPROVED RESPIRATORY DEVICE.
======================================
Handling and Storage Precautions:STORE IN COOL WELL VENTILATED SPACE. Other Precautions:USE A SELF-CONTAINED BREATHING APPRATUS IF ENTRY INTO A STOREAGE TANK OR VESSEL IS REQUIRED.

==========

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH EXPOSURE OF CONCERN. Ventilation:MECHANICAL/GENERAL Protective Gloves:NEOPRENE Eye Protection:PROTECTIVE GOGGLES. Supplemental Safety and Health PHILLIPS PETROLEYM CO MFR'S RAW MATERIAL,BURDICK & JACKSON LAB REFINES TO DESIRED PCT.SPEC & GRADE, CONTAINER SIZE: 1 GAL BOTTLE.

HCC:F2 Boiling Pt:B.P. Text:152F/66C Vapor Pres:130 Vapor Densi ty:3.0 Spec Gravity:0.67 Evaporation Rate & amp; Reference:0.3(ETHYL ETHER) Solubility in Water:NEGLIGIBLE Appearance and Odor:WATER-WHITE NON-VISCOUS LIQUID-MILD ODOR. Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES

Waste Disposal Methods:CONTROLLED BURNING AT A SAFE LOCATION. COMPLY WITH LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situatio n.