

GENERAL ELECTRIC CO CAPACITOR PROD DIV -- 17F366 -- 5910-00-961-6014

=====
Product Identification
=====

Product ID:17F366

MSDS Date:01/01/1985

FSC:5910

NIIN:00-961-6014

MSDS Number: BFZHP

=== Responsible Party ===

Company Name:GENERAL ELECTRIC CO CAPACITOR PROD DIV

Address:JOHN ST

City:HUDSON FALLS

State:NY

ZIP:12839

Country:US

Emergency Phone Num:518-746-5750

CAGE:01002

=== Contractor Identifica

tion ===

Company Name:GENERAL ELECTRIC CO CAPACITOR PRODUCTS DEPARTMENT

Address:JOHN ST

Box:City:HUDSON FALLS

State:NY

ZIP:12839

Country:US

Phone:518-746-5750

CAGE:01002

=====
Composition/Information on Ingredients
=====

Ingred Name:POLYCHLORINATED BIPHENYLS (PCBS) (SARA III)

CAS:1336-36-3

RTECS #:TQ1350000

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

=====
Hazards Identification
=====

Effects of Overexposure:INHAL:RESP TK IRRIT;

SKIN/EYE;IRRIT,I

NFLAM,CHLORACNE; MAY CAUSE LIVER DAMAGE

=====
First Aid Measures
=====

First Aid:INHAL:RMV TO FRESH AIR. IF NOT BRTHNG GIVE CPR. IF BRTHNG
DIFF, GIVE OXYGEN. EYES:IMMED FLUSH W/PLENTY OF WATER. SKIN:WASH
W/SOAP&WATER. RMV CONTAM CLTHNG&SHOES. INGEST:INDUCE VOMIT.RPT
UNTIL VOMIT IS CLEAR.

=====
Fire Fighting Measures
=====

Flash Point:NONE

Extinguishing Media:EXTINGUISH W. AGENT SUITABLE FOR SURROUNDING FIRE.

Fire Fighting Procedures:WEAR CHEMICAL PROTECTIVE SUIT WITH SELF CONTD
BRTHG APP.

Unusual Fire/Explosion Hazard:MATL IS NON-FLAMMABLE BUT MAY GENERATE
TOXIC GASES IN HEAT OF FIRE

=====
Accidental Release Measures
=====

Spill Release Procedures:EVAC NON-ESSENTL PERSONNEL. VENT SPIL AREA.
WEAR PROTECT EQUIPT. STOP LEAK. SOAK UP LIQUID W/NON-REACTIVE MATL
(SAND, DIRT, ETC) OR RMV BY DIKE & PUMPING OR OTHER SUITABLE MEANS.
CLEAN AREA W/SUITABLE SAF
ETY SOLVENT. LAUNDER CONTAMINATED CLTHNG.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED
AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP
CONTAINERS TIGHTLY CLOSED

Other Precautions:CHLORODIPHENYLS MAY ATTACK SOME TYPES OF RUBBER AND
PLASTIC. DO NOT USE CONTAMINATED WORK CLOTHING. WASH/SHOWER AFTER
EXPOSURE TO PCB'S

=====
Exposure Controls/Personal Protection ==
=====

Respiratory Protection:NIOSH/MESA APPR SCBA/AIR SUPP RESPIR.

Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV.

Protective Gloves:IMPERVIOUS

Eye Protection:GOGGLES/FACE SHIELD

Other Protective Equipment:WEAR FULL PROTECTIVE CLOTHING.

Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:Z3

Solubility in Water:NEGLIGIBLE

Appearance and Odor:PALE YELLOW VISCOUS LIQUID W/HYDROCARBON ODOR

=====
Stability and Reactivity Data

=====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid: SEE OTHER PRECAUTIONS

Hazardous Decomposition Products: HYDROGEN CHLORIDE, CO, & OTHER
TOXIC/IRRITATING GASES/FUMES.

===== Disposal Considerations =====

Waste Disposal Methods: CONTROLLED DISPOSAL RQD. GEN. V. HIGH TEMP
INCINERATION. IAW ALL LOCAL, STATE, & FEDERAL REGULATIONS.
PERMITTED DISPOSAL OPERATOR REQUIRED.

Disclaimer (provided w

ith this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.