

DOW CORNING CORPORATION -- MOLYKOTE G-N PASTE -- 8030-00-964-6407

=====
Product Identification
=====

Product ID:MOLYKOTE G-N PASTE

MSDS Date:01/01/1985

FSC:8030

NIIN:00-964-6407

MSDS Number: BFZMK

=== Responsible Party ===

Company Name:DOW CORNING CORPORATION

Emergency Phone Num:(517) 496-5900

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box

:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY8030000

Fraction by Wt: 50%

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:MOLYBDENUM DISULFIDE

CAS:131

7-33-5
RTECS #:QA4697000
Fraction by Wt: 17%
OSHA PEL:10 MG/M3 TDUST (MO)
ACGIH TLV:10 MG/M3 (MO); 8990

Ingred Name:ZINC PHOSPHATE
Fraction by Wt: 15%

Ingred Name:CALCIUM PHOSPHATE
Fraction by Wt: 15%

Ingred Name:WAX
CAS:8002-74-2
RTECS #:RV0350000
Fraction by Wt: 3%

===== Hazards Identification =====

Effects of Overexposure:IRRITATES EYES

===== First Aid Measures =====

First Aid:EYE CONTACT:IMMEDIATELY FLUSH W/WATER
FOR AT LEAST 15 MINS.

===== Fire Fighting Measures =====

Flash Point:>250F/121C OC
Extinguishing Media:CO*2, FOAM
Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS &
PROTECTIVE CLOTHING
Unusual Fire/Explosion Hazard:NONE KNOWN TO MFG

===== Accidental Release Measures =====

Spill Release Procedures:USE ABSORBENT MATERIAL TO COLLECT AND CONTAIN
FOR SALVAGE OR DISPOSAL

===== Exposure Controls/Personal Prot

ection =====

Respiratory Protection:MFG SUGGESTS-NONE SHOULD BE NEEDED

Ventilation:MECHANICAL-RECOMMENDED

Eye Protection:SAFETY GLASSES

Supplemental Safety and Health

VAPOR PRESS:L