

LOCTITE CORP -- LOCTITE GRADE C ANAEROBIC ADHESIVE, 250CC C, 8441 -- 8030-00-964-7537

=====  
Product Identification  
=====

Product ID:LOCTITE GRADE C ANAEROBIC ADHESIVE, 250CC C, 8441

MSDS Date:05/24/1991

FSC:8030

NIIN:00-964-7537

MSDS Number: BFZMP

=== Responsible Party ===

Company Name:LOCTITE CORP

Address:705-NORTH MOUNTAIN ROAD

City:NEWINGTON

State:CT

ZIP:06111-1411

Country:US

Info Phone Num:20

3-278-1280

Emergency Phone Num:203-278-1280

Preparer's Name:STEPHEN REPETTO

CAGE:7K128

=== Contractor Identification ===

Company Name:LOCTITE CORP

Address:705 N MT RD

City:NEWINGTON

State:CT

ZIP:06111

Country:US

Phone:312-689-6200

CAGE:7K128

Company Name:LOCTITE CORPORATION

Address:1001 TROUT BROOK CROSSING

Box:City:ROCKY HILL

State:CT

ZIP:06067-3910

Country:US

Phone:860-571-5100

CAGE:05972

=====  
Composition/Information on Ingredients  
=====

Ingred Name:TRIBUTYL AMINE (APPROX

2.0%)

Ingred Name:ORGANIC HYDROPEROXIDE  
Fraction by Wt: 10,000 M/KG-ACCORDING TO MFG.

===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:>200F,>93C  
Lower Limits:0.8%  
Upper Limits:6.4%  
Extinguishing Media:CO\*2, DRY CHEMICAL, FOAM  
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA AND FULL  
PROTECTIVE EQUIPMENT .  
Unusual Fire/Explosion Hazard:IRRITATING ORGANIC VAPORS FORMED BY FIRE  
OR THERMAL DECOMPOSITION.

===== Ac  
cidental Release Measures =====

Spill Release Procedures:FLUSH W/SLVENTS, TAKING PRECAUTIONS FOR  
POSSIBLE VAPORS & FIRE HAZARD OF SOLVENT USED. MIL-SPEC RECOMMENDS  
WIPING OFF APILL W/A CLOTH MOISTENED W/WATER OR TRICHLOROETHYLENE.

===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 110F, TO RETAIN SHELF LIFE  
Other Precautions:AVOID PROLONGED SKIN CONTACT

===== Exposure Controls/Personal Protection ==  
=====

Protective Gloves:RECOMMENDED  
Eye Protection:RECOMMENDED  
Supplemental Safety and Health  
VAP PRESS: 300F  
Vapor Pres: