

H. R. SIMON & CO., INC. -- S50-161,H.S.FIXER PART A -- 6750-00-965-4843

=====
Product Identification
=====

Product ID:S50-161,H.S.FIXER PART A

MSDS Date:01/01/1987

FSC:6750

NIIN:00-965-4843

MSDS Number: BFZVG

=== Responsible Party ===

Company Name:H. R. SIMON & CO., INC.

Emergency Phone Num:301 636 5555

CAGE:MO396

=== Contractor Identification ===

Company Name:H. R. SIMON & CO., INC.

CAGE:MO396

C

Company Name:SIMON H R CO,INC.

Address:3515 MARMENCO COURT

Box:City:BALTIMORE

State:MD

ZIP:21230-3411

Country:US

Phone:410-636-5555

CAGE:27912

=====
Composition/Information on Ingredients
=====

Ingred Name:ACETIC ACID (SARA III)

CAS:64-19-7

RTECS #:AF1225000

Fraction by Wt: 07.5%

OSHA PEL:10 PPM

ACGIH TLV:10 PPM/15 STEL; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:AMMONIUM THIOSULFATE; CAS #7783-18-8; WT % RANGE:40-50%

CAS:7783-18-8

RTECS #:XN6465000

Fraction

by Wt: 45.0%

Ingred Name:SODIUM BISULFITE (SASA III)

CAS:7631-90-5

RTECS #:VZ2000000

Fraction by Wt: 03.0%

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:WATER; CAS #7732-18-5

CAS:7732-18-5

RTECS #:ZC0110000

=====
===== Hazards Identification =====
=====

Effects of Overexposure:EYES/SKIN:MOD TO SEV IRRIT.MAY CAUSE ALLERGIC REACTION ON PROLONGED CONTACT.

=====
===== First Aid Measures =====
=====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H*2O FOR 15 MIN;INGEST:RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE.

=====
===== Fire Fighting Measures =====
=====

Flash Point:NONE

Extinguishing Media:EXTINGUISH WITH AGENT SUITABLE FOR SURROUNDING FIRE

Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*2O SPRAY TO COOL CONTR.

Unusual Fire/Explosion Hazard:NO
NE NOTED BY MANUFACTURER.

=====
===== Accidental Release Measures =====
=====

Spill Release Procedures:ELIMINATE IGNITION SOURCES. STOP LEAK. EVACUATE AREA.DO NOT TOUCH SPILLAGE. SM SPILL:ABSORB W. INERT ABSORBENT. PLACE IN CLOSED CONTAINER. FLUSH AREA W. WATER. LG SPILL: DIKE AHEAD FOR LATER DISPOSAL. NOTIFY AUTHORITIES.

=====
===== Handling and Storage =====
=====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA

. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP
CONTAINERS TIGHTLY CLOSED

Other Precautions:STORE BETWEEN 40F-90F; DO NOT BREATHE VAPORS/MIST.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT NEEDED

Ventilation:LOCAL OR MECHANICAL GENERALLY ADEQUATE

Protective Gloves:RUBBER

Eye Protection:SAFETY/CHEM GOGGLES

Other Protective Equipment:NORMAL WORK CLOTHING COVERING ARMS & LEGS.

Supplemental Safety and Health

MSDS NOT DAT

ED. THIS DESCRIBES PART A; KEY1:Z01

=====
===== Physical/Chemical Properties =====

HCC:C3

Boiling Pt:B.P. Text:>212F/100C

Vapor Pres:16

Spec Gravity:1.33

Solubility in Water:COMPLETE

Appearance and Odor:CLEAR COLORLESS LIQUID,AMMONIA SMELL

Percent Volatiles by Volume:60

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ALKAIS

Stability Condition to Avoid:EXCESSIVE HEAT

Hazardous Decomposition Products:A

MMONIA, OXIDES OF N,S & C IF INVOLVED
IN FIRE/COMBUSTION.

=====
===== Disposal Considerations =====

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE &
DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE
INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no

manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.