Product ID:PHOTICA 130F RAPID FIXER

MSDS Date:01/01/1987

FSC:6750

NIIN:00-965-4843

MSDS Number: BFZVH
=== Responsible Party ===
Company Name:PHOTICA INC
Address:491 LYONS AVE

City: IRVINGTON

State:NJ

ZIP:07111-4717 Country:US

CAGE:KO586

=== Contractor Identification === Company Name: PHOTICA INC

Address:4

91 LYONS AVE

Box:City:IRVINGTON

State:NJ

ZIP:07111-4717

Country:US

Phone:201-705-9553 (KROMICA)

CAGE:KO586

Company Name: PHOTICA INC (WAS PURCHASED BY KROMICA INC.)

Address:491 LYONS AVE Box:City:IRVINGTON

State:NJ

ZIP:07111-4717

Country:US

Phone:201-926-1000 (KRONICA INC.)

CAGE:60349

======= Composition/Information on Ingredients ========

Ingred Name: AMMONIUM THIOSULFATE

CAS:7783-18-8

RTECS #:XN6465000 Fraction by Wt: 50%

Ingred Name:SODIUM ACETATE

CAS:126-96-5

RTECS #:AJ4375000

Ingred Name: ACETIC ACID (SARA III) CAS:64-19-7 RTECS #:AF1225000 Fraction by Wt: 2% **OSHA PEL:10 PPM** ACGIH TLV:10 PPM/15 STEL; 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS =========== Hazards Identification ========================== Effects of Overexposure: AVOID CONTACT WITH SKIN, EYES, CLOTHING. CONTACT W/ANY TISSUE MAY CAUSE IRRITATION. First Aid:EYES: FLUSH WITH WATER 15 MIN & OBTAIN MEDI CAL ATTENTION. SKIN: WASH THOROUGHLY WITH SOAP & WATER. Flash Point:NONE Fire Fighting Procedures: NONE-COMBUSTIBLE LIQUID ======== Accidental Release Measures ============ Spill Release Procedures: WEARING RUBBER GLOVES & GOGGLES, MOP UP SPILLS. RINSE & MOP SOILED AREA WITH FRESH WATER. ============= Handling and Storage ================= Handling and Storage Precautions:STORE CONTA **INERS IN DRY AREA BETWEEN** 40F(4C) & 85F(30C) ====== Exposure Controls/Personal Protection ======== Protective Gloves: RUBBER Eye Protection: GOGGLES/SAFETY GLASSES Supplemental Safety and Health PH=5.4 ======== Physical/Chemical Properties ============= HCC:N1 Boiling Pt:B.P. Text:>212F/100C Spec Gravity:1.34 Solubility in Water: COMPLETE Appearance and Odor:PALE YELLOW-GREEN LIQUID ======= Disposal Considerations ===========

Fraction by Wt: 6%

Waste Di

sposal Methods:FLUSH WASTE,SPENT OR EXCESS FIXER DOWN SANITARY SEWER DRAIN WITH COPIOUS AMOUNTS OF WATER.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional a dvice to verify and assume responsibility for the suitability of this information to their particular situation.