View NSN Online: https://aerobasegroup.com/nsn/9150-00-966-8831

GULF OIL PRODUCTS CO -- HARMONY 32, ARO PNEUMATIC LUBRICATING OIL, 29665 9150-00-966-8831

============= Product Identification ========================

Product ID:HARMONY 32, ARO PNEUMATIC LUBRICATING OIL, 29665

MSDS Date:09/18/1986

FSC:9150

NIIN:00-966-8831

MSDS Number: BFZXK === Responsible Party ===

Company Name: GULF OIL PRODUCTS CO

Box:2001

City:HOUSTON

State:TX ZIP:77252 Country:US

Info Phone Num:800-424-9300 (CHEM

TREC)

Emergency Phone Num:415-233-3737

CAGE:3X578

=== Contractor Identification ===

Company Name: GULF OIL CO U.S. A DIV OF GULF OIL CORP

Box:1519

City:HOUSTON

State:TX ZIP:77001 Country:US CAGE:34252

Company Name: GULF OIL PRODUCTS CO DIV OF GULF OIL CORP

Address:8554 KATY FWY

Box:4256

City:HOUSTON

State:TX ZIP:77210 Country:US CAGE:3X578

======= Composition/Information on Ingredients ========

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATE, SOLVENT DEWAXED (SEVERE), HEAVY PARAFF

INIC
CAS:64742-65-0
RTECS #:PY8038501
Fraction by Wt: 99%
OSHA PEL:N/K
ACGIH TLV:5 MG/M3 (MFR)

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE:EYE:LIQUID MAY CAUSE IRRITATION. EXCESSIVE EXPOSURE TO VAPORS, FUMES MISTS MAY CAUSE IRRITATION. SKIN:REPEATED AND/OR PROLONGE

D CONTACT MAY CAUSE IRRITATION AND/OR
DERMATITIS. INHALATION:REPEATE D OR PROLONGED EXPOSURE TO VAPORS,
FUMES OR MISTS MAY CAUSE IRRITATION OF RESPIRATORY TRACT. (EFTS OF
OVEREXP)

Explanation of Carcinogenicity: NOT RELEVANT.

Effects of Overexposure:HLTH HAZ:MASSIVE EXPOSURE TO VAPORS, FUMES OR MIST MAY CAUSE HEADACHE, DIZZINESS AND/OR DROWSINESS (CNS DEPRESSION). INGESTION:NOT EXPECTED TO BE ACUTELY TOXIC BY INGESTION. SIGNS & SYMPS OF RESP TRAC T IRRIT MAY INCL, BUT MAY NOT

LIM TO, ONE/MORE OF THE FOLLOWING, DEPENDING ON DOSE, LENGTH OF EXPOSURE. (SUPDAT)

Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid:INHAL:REMOVE TO FRESH AIR. SUPPORT BREATHING (GIVE O*2/ARTF RESP). EYES:FLUSH IMMEDIATELY W/FRESH WATER FOR @ LEAST 15 MINS WHILE HOLDING EYELIDS OPEN. IF IRRIT PERSISTS, SEE MD. SKIN:REMOVE CO NTAMD CLTHG. WASH THORO W/SOAP & WATER.IF IRRIT R SLTS, SEEK MED

AID. INGEST:IF SWALLOWED, GIVE WATER/MILK TO DRINK & TELEPHONE FOR MED ADIVSE. CONSULT MED PERS BEFORE INDUCING VOMIT. IF (SUPDAT)


Flash Point Method:COC

Flash Point:410F,210C

Extinguishing Media:CO*2, DRY CHEMICAL, FOAM, WATER FOG.

Fire Fighting Procedures: USE NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT.

Unusual Fire/Explosion Hazard:DO NOT WELD, HEAT/DRILL CNTNR. RESIDUE MAY IGNITE W



Stability Indicator/Materials to Avoid:YES
MAY REACT WITH STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:MAY REACT WITH STRONG OXIDIZING MATERIALS.
Hazardous Decomposition Products:NORMAL COMBUST FORMS CARBON DIOXIDE &
WATER VAP; INCOMPLETE COMBUST CAN PRODUCE CARBON MONOXIDE.

======= Disposal Considerations ===========

Waste Disposal Methods:INCIN UNDER CONTROLLED CNDTNS/DISPOSE OF IN SECURE CHEM LANDFILL (ABSORB MATL). DISPOSE OF THIS MATL I/A/W

LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.