

CONSOLIDATED MOTOR OIL,INC. -- CONSOLMO A/W HYDRAULIC OIL 46 -- 9150-00-966-8833  
===== Product Identification =====

Product ID:CONSOLMO A/W HYDRAULIC OIL 46  
MSDS Date:01/20/1989  
FSC:9150  
NIIN:00-966-8833  
MSDS Number: BFZXZ  
=== Responsible Party ===  
Company Name:CONSOLIDATED MOTOR OIL,INC.  
Address:1773 PINE AVE  
Box:427  
City:VINELAND  
State:NJ  
ZIP:08360-3442  
Country:US  
Info Phone Num:609-691-1066  
Em  
ergency Phone Num:609-691-1066  
CAGE:9Z316

=== Contractor Identification ===  
Company Name:CONSOLIDATED MOTOR OIL CO INC  
Address:1773 PINE AVE  
Box:427  
City:VINELAND  
State:NJ  
ZIP:08360-3442  
Country:US  
Phone:609-691-1066  
CAGE:9Z316

===== Composition/Information on Ingredients =====

Ingred Name:REFINED PETROLEUM OIL  
Fraction by Wt: >99%  
OSHA PEL:5 MG/M3 (OIL MIST)  
ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:ANTIWEAR RUST AND OXIDATION INHIBITOR ADDITIVES (CONTAINS  
ZINC DIALKYLDI

THIOPHOSPHATE)

Fraction by Wt: 15 G/KG

Routes of Entry: Inhalation:NO Skin:UNKNOWN Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:NONE NOTED.

Effects of Overexposure:EYES:IRRITATION. SKIN:DERMATITIS.

INGESTION:NAUSEA,VOMITING,DIARRHEA.

Medical Cond Aggravated by Exposure:NONE NOTED.

=====  
===== First Aid Measures =====

First Aid:EYES:FLUSH WITH LARGE AMOUNTS OF WATER. SKIN:WASH WITH SOAP  
AND WATER.REMO

VE CONTAMINATED CLOTHING. INGESTION:DO NOT INDUCE  
VOMITING.SEEK MEDICAL HELP.

=====  
===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:>424F,>218C

Extinguishing Media:FOAM,DRY CHEMICAL,CARBON DIOXIDE,WATER FOG.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND  
PROTECTIVE CLOTHING.USE WATER SPRAY TO COOL FIRE EXPOSED  
CONTAINERS.

Unusual Fire/Explosion Hazard:DIRECT WATER STREAM MAY CAUSE FROTHING.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:RECOVER FREE LIQUID.ABSORB REMAINING LIQUID IN  
INERT ABSORBENT AND PLACE IN APPROPRIATE DISPOSAL CONTAINER.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED  
AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP  
CONTAINERS TIGHTLY CLOSED

Other Precautions:DO NOT APPLY HEAT OR FLAME TO CONTAINERS.

=====

Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT REQUIRED.USE ORGANIC RESPIRATOR IN MIST CONCENTRATION.

Ventilation:NORMAL ROOM VENTILATION.

Protective Gloves:NITRILE.

Eye Protection:CHEM SPLASH GOGGLES

Other Protective Equipment:NORMAL WORK CLOTHING COVERING ARMS & LEGS.

Work Hygienic Practices:WASH HANDS AFTER HANDLING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health  
NONE.

===== Physical/Chemical Properties =====

HCC:V6

Vapor Pres:NEGLIGIBLE

Vapor Density:>1.0

Spec Gravity:0.88

Evaporation Rate & Reference:NEGLIGIBLE

Solubility in Water:NEGLIGIBLE

Appearance and Odor:AMBER COLOR LIQUID W/PETROLEUM OIL ODOR

Percent Volatiles by Volume:NEGLIG

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:NONE.

Hazardous Decomposition Products:FROM BURNING,EMITS CO,CO\*2,TRACE S

OXIDES OF S, P, & ZN.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE IN APPROVED INCINERATOR OR DISPOSE OF IN APPROVED CHEMICAL DUMP IN ACCORDANCE WITH LOCAL,STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants

this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.