

CONSOLIDATED MOTOR OIL,INC. -- CONSOLMO A/W HYDRAULIC OIL 46 -- 9150-00-966-8833
===== Product Identification =====

Product ID:CONSOLMO A/W HYDRAULIC OIL 46
MSDS Date:01/20/1989
FSC:9150
NIIN:00-966-8833
MSDS Number: BFZXZ
=== Responsible Party ===
Company Name:CONSOLIDATED MOTOR OIL,INC.
Address:1773 PINE AVE
Box:427
City:VINELAND
State:NJ
ZIP:08360-3442
Country:US
Info Phone Num:609-691-1066

Em
ergency Phone Num:609-691-1066

CAGE:9Z316
=== Contractor Identification ===
Company Name:CONSOLIDATED MOTOR OIL CO INC
Address:1773 PINE AVE
Box:427
City:VINELAND
State:NJ
ZIP:08360-3442
Country:US
Phone:609-691-1066
CAGE:9Z316

===== Composition/Information on Ingredients =====

Ingred Name:REFINED PETROLEUM OIL
Fraction by Wt: >99%
OSHA PEL:5 MG/M3 (OIL MIST)
ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:ANTIWEAR RUST AND OXIDATION INHIBITOR ADDITIVES (CONTAINS
ZINC DIALKYLDI

THIOPHOSPHATE)

Fraction by Wt: 15 G/KG

Routes of Entry: Inhalation:NO Skin:UNKNOWN Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:NONE NOTED.

Effects of Overexposure:EYES:IRRITATION. SKIN:DERMATITIS.

INGESTION:NAUSEA,VOMITING,DIARRHEA.

Medical Cond Aggravated by Exposure:NONE NOTED.

=====
===== First Aid Measures =====

First Aid:EYES:FLUSH WITH LARGE AMOUNTS OF WATER. SKIN:WASH WITH SOAP AND WATER.REMOVE CONTAMINATED CLOTHING. INGESTION:DO NOT INDUCE VOMITING.SEEK MEDICAL HELP.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:>424F,>218C

Extinguishing Media:FOAM,DRY CHEMICAL,CARBON DIOXIDE,WATER FOG.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING.USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

Unusual Fire/Explosion Hazard:DIRECT WATER STREAM MAY CAUSE FROTHING.

=====
===== Accidental Release Measures =====

Spill Release Procedures:RECOVER FREE LIQUID.ABSORB REMAINING LIQUID IN INERT ABSORBENT AND PLACE IN APPROPRIATE DISPOSAL CONTAINER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED

Other Precautions:DO NOT APPLY HEAT OR FLAME TO CONTAINERS.

=====

Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT REQUIRED.USE ORGANIC RESPIRATOR IN MIST CONCENTRATION.

Ventilation:NORMAL ROOM VENTILATION.

Protective Gloves:NITRILE.

Eye Protection:CHEM SPLASH GOGGLES

Other Protective Equipment:NORMAL WORK CLOTHING COVERING ARMS & LEGS.

Work Hygienic Practices:WASH HANDS AFTER HANDLING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health
NONE.

===== Physical/Chemical Properties =====

HCC:V6

Vapor Pres:NEGLIGIBLE

Vapor Density:>1.0

Spec Gravity:0.88

Evaporation Rate & Reference:NEGLIGIBLE

Solubility in Water:NEGLIGIBLE

Appearance and Odor:AMBER COLOR LIQUID W/PETROLEUM OIL ODOR

Percent Volatiles by Volume:NEGLIG

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:NONE.

Hazardous Decomposition Products:FROM BURNING,EMITS CO,CO*2,TRACE
S

OXIDES OF S, P, & ZN.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE IN APPROVED INCINERATOR OR DISPOSE OF IN APPROVED CHEMICAL DUMP IN ACCORDANCE WITH LOCAL,STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants

this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.